

# Bobbins (9677182209)



Part Number: 9677182209

77 BOBBIN 3PC. ASSEMBLY

Explanation of Part Numbers:

- Digits 1 & 2 = Product Class
- Digits 3 & 4 = Material Grade
- - Last digit 8 = Coated Bobbin

Bobbins are an economical and well- proven core design for many applications where relatively low but stable inductance values are required.

For higher frequency designs, use small bobbins in 43 material.

□  
For power applications, bobbins in 77 material are specified for  $A_L$  and dc bias limits.

Bobbins in Figures 2-5 can be supplied with a uniform thermo- set plastic coating which can withstand a minimum breakdown of 500Vrms. This coating will change the dimensions a maximum of 0.5 mm (0.020"). The last digit of the thermo- set plastic coated part is an "8".

□ **For any bobbin requirement not listed in the catalog, please contact our customer service group for availability and pricing.**

Weight: 14 (g)

Dim	mm	mm tol	nominal inch	inch misc.
A	18	±0.45	0.709	—
B	22	±0.70	0.866	—
D	14.5	±0.35	0.57	—
F	11	±0.30	0.433	—
G	2.5	±0.30	0.098	—
H	3.2	±0.10	0.126	—





Figure 4

**Chart Legend**

$A_L$  : Inductance Factor  NI : Value of dc Ampere- turns,  $A_w$ : Winding Area,  
N/ AWG : Number of Turns/ Wire Size for Test Coil

Electrical Properties	
$A_L$ (nH)	65 ±10%
$A_L$ min. @ NI (At)	55 - 410
N/ AWG	95/22
$A_w$ (cm <sup>2</sup> )	0.51

Bobbins are tested for  $A_L$  value at 1kHz < 10 gauss.