



## HWS150A-12/MEA

Sales Region	Worldwide
Series	HWS-A/ME
Status	Production
Feature	Medical for Medical instruments
Option	With cover type
	Approved by safety standards for medical equipment
Option Lineup	Please refer to here.
Recommended EMC Filter	Please refer to here.
Accessories	Please refer to the catalog



Electrical	Characteristics
Input Voltage Range[AC]	85 to 265V
Input Voltage Range[DC]	120 to 370V
Efficiency	88% Typ.
Rated Output Voltage[DC]	12V
Output Voltage Range[DC]	9.6 to 14.4V
Maximum Output Current	13A
Maximum Output Power	156W

Cases Shape & Size		
Case'[] shape	Unit	
Width(W)	42mm Nom.	
Height(H)	82mm Nom.	
Depth(D)	160mm Nom.	
Weight	520g Typ.	

Other		
Operating Temp. Range	-10 to 70°C	
Cooling	Convection cooling	
	ES60601-1	
Safety Standard(Certified)	EN60601-1	
	CSA-C22.2 No.60101-1	
Safety Standard(Conformed)		
Remarks	This page only shows representative characteristics. Please refer to the	
Refildiks	technical data for detailed specifications and conditions.	

! Images are for reference only and show exemplary products. ! This PDF document was created based on the data listed on the TDK Corporation website.

! All specifications are subject to change without notice.