

NAS1791C4-4 SELF-LOCKING PLATE NUT SPEC

Description:

Thread Size: 1/4", Nut Length: 1-1/4", Nut Height: 1/2"

NAS1791C4-4 Manufacturer certs (CofC) are provided free on all orders

Order this part online

Additional Information

| | |
|-------------------------|---|
| Gov. Issued Name: | Self-Locking Plate Nut |
| NSN: | 5310-01-090-6367 |
| NIIN: | 010906367 |
| FSC: | Nuts and Washers / 5310 |
| Associated NSN(s): | • 5310-01-106-7558 |
| Schedule B: | 7318.16.0000, Nuts of iron or steel |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |
| Manufacturer Country: | United States |

NAS1791C4-4 Specifications

| | |
|---|--|
| Center To Center Distance Between Mounting Holes Along Length: | 0.998 Inches Minimum And 1.002 Inches Maximum |
| Counterbore Diameter: | 0.254 Inches Nominal Nut |
| Distance From Aperture Center To Mounting Hole Center: | 0.495 Inches Minimum And 0.505 Inches Maximum |
| Features Provided: | Floating Nut |
| Material: | Iron Alloy 660 Nut |
| Material: | Iron Alloy 660 Shell |
| Mounting Hole Arrangement Style: | 2 Holes |
| Mounting Hole Diameter: | 0.098 Inches Minimum And 0.103 Inches Maximum |
| Nominal Thread Size: | 0.250 Inches |
| Nut Counterbore Depth: | 0.250 Inches Minimum Nut |
| Nut Length: | 1.292 Inches Maximum |
| Nut Height: | 0.481 Inches Maximum |
| Nut Mounting Provision: | Straight Holes |
| Nut Style: | Plate |
| Locking Feature: | Prevailing Torque All Metal Design |
| Lubrication: | Dry Film Lubricant |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Nut Or Ams 5732 Assn Std Single Material Response Nut Or Ams 5737 Assn Std Single Material Response Nut |
| Material Document And Classification: | Ams 5525 Assn Std Single Material Response Shell |
| Removable Nut Manufacturer Code: | 80205 |
| Removable Nut Manufacturer Part Number: | Nas1794c4-4 |
| Plate Thickness: | 0.027 Inches Minimum And 0.037 Inches Maximum |
| Plate Width: | 0.547 Inches Maximum |
| Specification/standard Data: | 80205-nas1791 Professional/industrial Association Standard |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Surface Treatment: | Passivate Overall |
| Temp Rating: | 450.0 Deg Fahrenheit Maximum |
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Thread Quantity Per Inch: | 28 |

Thread Series:

Unjf

How to Order

Order this self-locking plate nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking-nutplates/NAS1791C4-4 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.