


**Major Ratings and Characteristics**

| Characteristics                                  | Value      | Units            |
|--|------------|------------------|
| $I_{F(AV)}$ Rectangular waveform                 | 30         | A                |
| $V_{RRM}$  | 60         | V                |
| $I_{FSM}$ @tp=5 $\mu$ s sine                     | 1020       | A                |
| $V_F$ @15 Apk, $T_J=125^\circ\text{C}$ (per leg) | 0.56       | V                |
| $T_J$  | -55 to 150 | $^\circ\text{C}$ |

**Description/Features**

The STPS30L60CW center tap Schottky rectifier has been optimized for very low forward voltage drop, with moderate leakage. The proprietary barrier technology allows for reliable operation up to 150 $^\circ\text{C}$  junction temperature. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- 150 $^\circ\text{C}$   $T_J$  operation
- Center tap TO-247 package
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Very low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability



## Voltage Ratings

| Part number                                     | STPS30L60CW |
|---|-------------|
| $V_R$ Max. DC Reverse Voltage (V)               | 60          |
| $V_{RWM}$ Max. Working Peak Reverse Voltage (V) |             |

## Absolute Maximum Ratings

| Parameters  | Value | Units | Conditions   |
|---|-------|-------|--|
| $I_{F(AV)}$ Max. Average Forward Current<br>* See Fig. 5                          | 30    | A     | 50% duty cycle @ $T_C = 112^\circ\text{C}$ , rectangular wave form   |
| $I_{FSM}$ Max. Peak One Cycle Non-Repetitive Surge Current (Per Leg) * See Fig. 7 | 1020  | A     | Following any rated load condition and with rated $V_{RWM}$ applied  |
|   | 265   |       |  |
| $E_{AS}$ Non-Repetitive Avalanche Energy (Per Leg)                                | 13    | mJ    | $T_J = 25^\circ\text{C}$ , $I_{AS} = 1.50$ Amps, $L = 11.5$ mH   |
| $I_{AR}$ Repetitive Avalanche Current (Per Leg)                                   | 1.50  | A     | Current decaying linearly to zero in 1 $\mu\text{sec}$<br>Frequency limited by $T_J$ max. $V_A = 1.5 \times V_R$ typical |

## Electrical Specifications

| Parameters   | Value    | Units            | Conditions  |
|--|----------|------------------|---|
| $V_{FM}$ Max. Forward Voltage Drop (Per Leg) * See Fig. 1 (1)    | 0.60     | V                | @ 15A<br>$T_J = 25^\circ\text{C}$                                       |
|  | 0.80     | V                | @ 30A   |
|  | 0.56     | V                | @ 15A<br>$T_J = 125^\circ\text{C}$                                      |
|  | 0.70     | V                | @ 30A   |
| $I_{RM}$ Max. Reverse Leakage Current (Per Leg) * See Fig. 2 (1) | 0.48     | mA               | $T_J = 25^\circ\text{C}$  |
|  | 50 (typ) |                  | $T_J = 125^\circ\text{C}$   |
|  | 100      |                  | $V_R = \text{rated } V_R$   |
| $C_T$ Max. Junction Capacitance (Per Leg)                        | 720      | pF               | $V_R = 5V_{DC}$ , (test signal range 100Khz to 1Mhz) $25^\circ\text{C}$ |
| $L_S$ Typical Series Inductance (Per Leg)                        | 7.5      | nH               | Measured lead to lead 5mm from package body                             |
| dv/dt Max. Voltage Rate of Change                                | 10000    | V/ $\mu\text{s}$ | (Rated $V_R$ )  |

(1) Pulse Width < 300 $\mu\text{s}$ , Duty Cycle <2%

## Thermal-Mechanical Specifications

| Parameters  | Value            | Units                     | Conditions                           |
|---|------------------|---------------------------|--------------------------------------|
| $T_J$ Max. Junction Temperature Range                             | -55 to 150       | $^\circ\text{C}$          |                                      |
| $T_{stg}$ Max. Storage Temperature Range                          | -55 to 150       | $^\circ\text{C}$          |                                      |
| $R_{thJC}$ Max. Thermal Resistance Junction to Case (Per Leg)     | 2.20             | $^\circ\text{C}/\text{W}$ | DC operation * See Fig. 4            |
| $R_{thJC}$ Max. Thermal Resistance Junction to Case (Per Package) | 1.10             | $^\circ\text{C}/\text{W}$ | DC operation                         |
| $R_{thCS}$ Typical Thermal Resistance, Case to Heatsink           | 0.24             | $^\circ\text{C}/\text{W}$ | Mounting surface, smooth and greased |
| wt Approximate Weight   | 6 (0.21)         | g (oz.)                   |                                      |
| T Mounting Torque   | Min. 6 (5)       | Kg-cm (lbf-in)            | Non-lubricated threads               |
|   | Max. 12 (10)     |                           |                                      |
| Case Style  | TO-247AC (TO-3P) | JEDEC                     |                                      |




Fig. 1 - Max. Forward Voltage Drop Characteristics (Per Leg)




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage (Per Leg)




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage (Per Leg)




Fig. 4 - Max. Thermal Impedance  $Z_{thJC}$  Characteristics (Per Leg)




Fig. 5 - Max. Allowable Case Temperature Vs. Average Forward Current (Per Leg)




Fig. 6 - Forward Power Loss Characteristics (Per Leg)




Fig. 7 - Max. Non-Repetitive Surge Current (Per Leg)




Fig. 8 - Unclamped Inductive Test Circuit

Data and specifications subject to change without notice.  
This product has been designed and qualified for Industrial Level.  
Qualification Standards can be found on IR's Web site.

International  
**IOR** Rectifier

**IR WORLD HEADQUARTERS:** 233 Kansas St., El Segundo, California 90245, USA Tel: (310) 252-7105  
TAC Fax: (310) 252-7309  
Visit us at [www.irf.com](http://www.irf.com) for sales contact information. 05/01