

## 2N5397, 2N5398

## N-Channel Silicon Junction Field-Effect Transistor

- Low-Noise
- High Power Gain
- High Transconductance
- Mixers
- Oscillators
- VHF Amplifiers

Absolute maximum ratings at  $T_A = 25^\circ\text{C}$ 

Reverse Gate Source & Reverse Gate Drain Voltage	- 25 V
Drain Source Voltage	25 V
Continuous Forward Gate Current	10 mA
Continuous Device Power Dissipation	300 mW
Power Derating	1.7 mW/°C

At 25°C free air temperature:

## Static Electrical Characteristics

		2N5397		2N5398		Unit	Process NJ26L	
		Min	Max	Min	Max		Test Conditions	
Gate Source Breakdown Voltage	$V_{(BR)GSS}$	- 25		- 25		V	$I_G = - 1 \mu\text{A}, V_{DS} = \emptyset\text{V}$	
Gate Source Forward Voltage	$V_{GS(F)}$		1		1	V	$I_G = 1 \text{ mA}, V_{DS} = \emptyset\text{V}$	
Gate Reverse Current	$I_{GSS}$		- 0.1		- 0.1	nA	$V_{GS} = - 15\text{V}, V_{DS} = \emptyset\text{V}$	
			- 0.1		- 0.1	$\mu\text{A}$	$V_{GS} = - 15\text{V}, V_{DS} = \emptyset\text{V}$	
Gate Source Cutoff Voltage	$V_{GS(OFF)}$	- 1	- 6	- 1	- 6	V	$V_{DS} = 10\text{V}, I_D = 1 \text{ nA}$	
Drain Saturation Current (Pulsed)	$I_{DSS}$	10	30	5	40	mA	$V_{DS} = 10\text{V}, V_{GS} = \emptyset\text{V}$	

## Dynamic Electrical Characteristics

Common Source Forward Transconductance	$g_{fs}$	5.5	9	5	10	mS	$V_{DG} = 10\text{V}, I_D = 10 \text{ mA}$	$f = 450 \text{ MHz}$
Common Source Forward Transfer Admittance	$ Y_{fs} $	6	10	5.5	10	mS	$V_{DS} = 10\text{V}, I_D = 10 \text{ mA}$	$f = 1 \text{ kHz}$
Common Source Output Conductance	$ g_{os} $		0.4		0.5	mS	$V_{DG} = 10\text{V}, I_D = 10 \text{ mA}$	$f = 450 \text{ MHz}$
Common Source Input Admittance	$ Y_{os} $		0.2		0.4	mS	$V_{DS} = 10\text{V}, I_D = 10 \text{ mA}$	$f = 1 \text{ kHz}$
Common Source Input Conductance	$g_{is}$		2		3	mS	$V_{DG} = 10\text{V}, I_D = 10 \text{ mA}$	$f = 450 \text{ MHz}$
Common Source Input Capacitance	$C_{iss}$		5		5.5	pF	$V_{DG} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1 \text{ kHz}$
Common Source Reverse Transfer Capacitance	$C_{rss}$		1.2		1.3	pF	$V_{DG} = 15\text{V}, V_{GS} = \emptyset\text{V}$	$f = 1 \text{ kHz}$

## TO-72 Package

Dimensions in Inches (mm)

## Pin Configuration

1 Source, 2 Drain, 3 Gate, 4 Case

## Surface Mount

SMP5397, SMP5398



1000 N. Shiloh Road, Garland, TX 75042  
(972) 487-1287 FAX (972) 276-3375

[www.interfet.com](http://www.interfet.com)