



PIN	CONNECTION
1	Control voltage
7	Ground
8	Output
14	Supply

Scale 1:1

## Features

- ▶▶▶▶ **3.3V supply**
- ▶▶▶▶ **Low cost for volume applications**
- ▶▶▶▶ **Choice of pullability & stability**
- ▶▶▶▶ **Express deliveries for non-standard items**
- ▶▶▶▶ **Industrial temperature range option**

## Specifications

Parameters	Product	Option Codes
	GVXO-44F	
<b>Package:</b> 14 pin DIL (full size)	■	
<b>Frequency range:</b> 33.0 ~ 125MHz	■	
<b>Voltage control:</b> +1.65V ±1.65V, 10% linearity > 100kΩ input impedance	■ ■	
<b>Frequency pullability (min):</b> ±50ppm ±100ppm ±150ppm	 □ ■ □	 N S W
<b>Frequency stability:</b> ±100ppm ±50ppm ±25ppm ±20ppm ±15ppm	 □ □ ■ □ □	 A B C D E
<b>Ageing:</b> ±5.0ppm max per year	■	
<b>Operating temperature range:</b> -10 to +70°C -40 to +85°C	■ □	 I
<b>Storage temperature range:</b> -55 to +125°C	■	
<b>Supply voltage (V<sub>DD</sub>):</b> +3.3V (±5%)	■	
<b>Supply current:</b> 18mA max (33.0 ~ 45.0MHz) 20mA max (>45.0 ~ 80.0MHz) 25mA max (>80.0 ~ 125MHz)	■ ■ ■	
<b>Driving ability:</b> 30pF HCMOS 5 LSTTL	■ ■	
<b>Logic levels:</b> '0' level = +0.4V max '1' level = 90%V <sub>DD</sub> min	■ ■	
<b>Waveform symmetry @ 50%V<sub>DD</sub>:</b> 40:60 max	■	
<b>Rise / fall time:</b> 5ns max (0.4V ~ 90%V <sub>DD</sub> min)	■	

■ Standard. □ Optional - Please specify required code(s) when ordering

## Ordering Information

Product + option codes + frequency  
 eg: **GVXO-44F/SC 49.1520MHz** ±100ppm pullability, ±25ppm stability  
 Option codes must be included to specify a model completely.  
 Option code X (eg GVXO-44F/X) denotes a custom spec.

♦ ±15ppm and ±20ppm stability may not be available over -40+85°C, depending on frequency. Check with our sales office.