


SBD Type : FSH10A10

OUTLINE DRAWING

FEATURES

- *Similar to TO-220AC Case
- *Fully Molded Isolation
- *Low Forward Voltage Drop
- *Low Power Loss, High Efficiency
- *High Surge Capability
- * $T_j=150\text{ }^\circ\text{C}$ operation



Maximum Ratings



Approx Net Weight: 1.7g

Rating	Symbol	FSH10A10		Unit
Repetitive Peak Reverse Voltage	V_{RRM}	100		V
Average Rectified Output Current	I_O	10	$T_c=120^\circ\text{C}$ 50 Hz half Sine Wave Resistive Load	A
RMS Forward Current	$I_{F(RMS)}$	15.7		A
Surge Forward Current	I_{FSM}	180	50Hz Half Sine Wave ,1cycle Non-repetitive	A
Operating Junction Temperature Range	T_{jw}	-40 to +150		$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-40 to +150		$^\circ\text{C}$
Mounting torque	F_{tor}	recommended torque = 0.5		N•m


Electrical • Thermal Characteristics

Characteristics	Symbol	Conditions	Min.	Typ.	Max.	Unit
Peak Reverse Current	I_{RM}	$T_j= 25^\circ\text{C}$, $V_{RM}= V_{RRM}$	-	-	1	mA
Peak Forward Voltage	V_{FM}	$T_j= 25^\circ\text{C}$, $I_{FM}= 10\text{ A}$	-	-	0.88	V
Thermal Resistance	$R_{th(j-c)}$	Junction to Case	-	-	3	$^\circ\text{C/W}$
	$R_{th(c-f)}$	Case to Fin	-	-	1.5	$^\circ\text{C/W}$


FSH_A_ OUTLINE DRAWING (Dimensions in mm)



FORWARD CURRENT VS. VOLTAGE




AVERAGE FORWARD POWER DISSIPATION



PEAK REVERSE CURRENT VS. PEAK REVERSE VOLTAGE


$T_j = 150\text{ }^\circ\text{C}$

FSH10A10/FSH10A10B



AVERAGE REVERSE POWER DISSIPATION

FSH10A10/FSH10A10B






AVERAGE FORWARD CURRENT VS. CASE TEMPERATURE

$V_{RM} = 100V$


FSH10A10/FSH10A10B



SURGE CURRENT RATINGS

$f = 50\text{Hz}$, Half Sine Wave, Non-Repetitive, No Load

FSH10A10/FSH10A10B



JUNCTION CAPACITANCE VS. REVERSE VOLTAGE

$T_j=25^\circ\text{C}$, $V_m=20\text{mV}_{\text{RMS}}$, $f=100\text{kHz}$, Typical Value

FSH10A10/FSH10A10B

