

Features

1. Effective in suppressing noise at high frequencies.
2. Suited for preventing the abnormal oscillation from high frequency amplifying circuits.
3. Excellent solder heat resistance for soldering.
4. High reliability in the circuits of high current.
5. Lead Free (RoHS Compliance)

Applications

1. Noise suppression in digital equipments.
2. Computers and peripheral devices, VCR and camera.
3. Noise suppression in automotive electronic equipment, car stereo, car engine controller.
4. Noise suppression for OA electronic instruments.

Ordering Information

SHB - **1** **M** **4532** - **121** **J** **T**
 (1) (2) (3) (4) (5) (6)

(1) Series

SHB : For Signal line

(2) Material & Design

M : For high impedance type
T : For Low speed

(3) Dimension

First two digits : length (mm)
Last two digits : width (mm)

(4) Impedance (at 100MHz)

First two digits are impedance values.
Last digit is the number of zeros


(5) Termination

J : Nickel barrier

(6) Packaging

B : Bulk package
T : Tape & Reel (Φ178mm [7 inches])
L : Tape & Reel (Φ254mm [10 inches])

Shape and Dimensions



Unit : mm [inches]

Type	L	W	T	C
SHB-1□4532-	4.5±0.25 (.177±.010)	3.2±0.25 (.126±.010)	1.3±0.25 (.051±.010)	0.70±0.40 (.027±.016)

Electrical Parameters

Part No.	Z at 100MHz(Ω)		DC Resistance (Ω) max.	Rated current (mA) max.
	typ.	min.		
SHB-1M4532-121□□	120	90	0.04	600
SHB-1M4532-151□□	150	115	0.04	600
SHB-1T4532-800□□	80	60	0.04	600
SHB-1T4532-121□□	120	90	0.04	600

- ※ Parts with other electrical characteristics available upon request.
- ※ Test equipment : HP4291 + HP16192A

Electrical Characteristic Curves

