

Sonardyne UK (Head Office)
T. +44 (0) 1252 872288
F. +44 (0) 1252 876100
E. sales@sonardyne.com
www.sonardyne.com

Datasheet

Compatt 5 Back Deck Test PDA





Description

Pocket Test Terminal is a new truly portable Compatt 5 test tool. Running on a dedicated iPAQ PDA platform, the Pocket Test Terminal software offers all the main features of the PC-based Compatt 5 Test Terminal software but from a small, portable, splash proof device. It is therefore ideal for taking on to the back deck to set-up and test Compatt 5s prior to and after deployment.

Splash-proof, ruggedised case protects the PDA in the back deck environment.

Portability simplifies deck testing and also warehouse stock checking.

Key Features

- Acoustic Wideband checks (Compatt to Compatt): Transducer, receiver & transmit
- Run internal Compatt self-test checks
- Battery check
- Read Compatt internal and external sensors
- Open and close the release
- Change Compatt address
- All test records are stored in the PDA and can be transferred to a PC for printing and/or filing.
- Software and Test Records stored in Flash memory to protect against a flat battery



Sonardyne UK (Head Office)
T. +44 (0) 1252 872288
F. +44 (0) 1252 876100
E. sales@sonardyne.com
www.sonardyne.com

Specifications Compatt 5 Back Deck Test PDA

Feature		Type 8049
Communications		RS232, Bluetooth, Serial IR
Processor		Intel® PXA270 Processor 312 MHz
Memory		128 MB total memory
Display		3.5" transflective TFT QVGA colour, 64K colours
Weight		550g (1.2lb)
Power	Battery	Removable/Rechargeable 920 mAh Lithium-lon
	A/C Power	AC Input: 100~240 Vac, 50/60 Hz, AC Input current: 0.3 A max;
		Output Voltage: 5Vdc (typical), Output Current: 2A (typical)
Dimensions (LxWxH)		210mm (8.3") x 114mm (4.5") x56mm (2.2")

