



SAW Components

SAW RF filter

Short range devices

Series/type:	B4147
Ordering code:	B39841B4147U410
Date:	April 29, 2008
Version:	2.1



SAW Components

B4147

SAW RF filter

836.50 MHz

Data sheet

SMD

Application

- Low-loss RF filter for mobile telephone AMPS systems, transmit path
- Usable passband 25 MHz
- No matching network required for operation at 50 Ω




Features

- Package size 3.0 x 3.0 x 1.1 mm³
- Package code DCC6C
- RoHS compatible
- Approximate weight 0.037 g
- Package for **Surface Mount Technology (SMT)**
- Ni, gold-plated terminals
- Lead free soldering compatible with J - STD20C
- AEC-Q200 qualified component family
- **Electrostatic Sensitive Device (ESD)**



Pin configuration

- 2 Input
- 5 Output
- 1, 3, 4, 6 Ground, to be grounded



Please read *cautions and warnings and important notes* at the end of this document.



SAW Components

B4147

SAW RF filter

836.50 MHz

Data sheet



Characteristics

Reference temperature: $T_A = +25\text{ }^\circ\text{C}$
 Terminating source impedance: $Z_S = 50\ \Omega$
 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ.	max.	
Center frequency	f_C	—	836.50	—	MHz
Maximum insertion attenuation	α_{\max}	—	2.7	3.0	dB
824.00 ... 849.00 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	1.7	2.0	dB
824.00 ... 849.00 MHz					
VSWR		—	1.78	1.92	
	824.00 ... 849.00 MHz				
Attenuation	α				
	0.00 ... 779.00 MHz	31	34	—	dB
	779.00 ... 805.00 MHz	25	31	—	
	869.00 ... 894.00 MHz	40	44	—	
	894.00 ... 979.00 MHz	36	40	—	
	979.00 ... 1030.00 MHz	38	40	—	
	1030.00 ... 1300.00 MHz	36	39	—	
	1300.00 ... 1580.00 MHz	28	32	—	
	1580.00 ... 1698.00 MHz	24	30	—	
	1698.00 ... 2547.00 MHz	14	22	—	
Rx band suppression	α				
	869.00 ... 894.00 MHz	40	44	—	dB



SAW Components	B4147
SAW RF filter	836.50 MHz

Data sheet



Characteristics

Temperature range for specification: $T_A = -30\text{ °C to }+85\text{ °C}$
 Terminating source impedance: $Z_S = 50\ \Omega$
 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ.	max.	
Center frequency	f_C	—	836.50	—	MHz
Maximum insertion attenuation	α_{\max}	—	3.0	3.5	dB
824.00 ... 849.00 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	2.0	2.5	dB
824.00 ... 849.00 MHz					
VSWR		—	1.78	1.92	
Attenuation	α				
0.00 ... 779.00 MHz		31	34	—	dB
779.00 ... 805.00 MHz		25	31	—	dB
869.00 ... 894.00 MHz		40	43	—	dB
894.00 ... 979.00 MHz		36	40	—	dB
979.00 ... 1030.00 MHz		38	40	—	dB
1030.00 ... 1300.00 MHz		36	39	—	dB
1300.00 ... 1580.00 MHz		28	32	—	dB
1580.00 ... 1698.00 MHz		24	30	—	dB
1698.00 ... 2547.00 MHz		14	22	—	dB
Rx band suppression	α				
869.00 ... 894.00 MHz		40	43	—	dB



SAW Components	B4147
SAW RF filter	836.50 MHz

Data sheet



Characteristics

Temperature range for specification: $T_A = -40\text{ °C to }+85\text{ °C}$
 Terminating source impedance: $Z_S = 50\ \Omega$
 Terminating load impedance: $Z_L = 50\ \Omega$

		min.	typ.	max.	
Center frequency	f_C	—	836.50	—	MHz
Maximum insertion attenuation	α_{max}	—	3.1	3.7	dB
824.00 ... 849.00 MHz					
Amplitude ripple (p-p)	$\Delta\alpha$	—	2.1	2.7	dB
824.00 ... 849.00 MHz					
VSWR		—	1.80	1.97	
Attenuation	α				
0.00 ... 779.00 MHz		31	34	—	dB
779.00 ... 805.00 MHz		25	31	—	dB
869.00 ... 894.00 MHz		40	43	—	dB
894.00 ... 979.00 MHz		36	40	—	dB
979.00 ... 1030.00 MHz		38	40	—	dB
1030.00 ... 1300.00 MHz		36	39	—	dB
1300.00 ... 1580.00 MHz		28	32	—	dB
1580.00 ... 1698.00 MHz		24	30	—	dB
1698.00 ... 2547.00 MHz		14	22	—	dB
Rx band suppression	α				
869.00 ... 894.00 MHz		40	43	—	dB

Maximum ratings

Operable temperature range	T_A	-40/+85	°C	
Storage temperature range	T_{stg}	-40/+85	°C	
DC voltage	V_{DC}	5	V	
Input power max.	P_{IN}	16	dBm	CDMA signal


Please read *cautions and warnings and important notes* at the end of this document.




Data sheet



Transfer function (narrowband measurement)



Transfer function (wideband measurement)





Please read *cautions and warnings* and *important notes* at the end of this document.





Reflection functions (measurement)

S_{11}



S_{22}





SAW Components **B4147**

SAW RF filter **836.50 MHz**

Data sheet



References

Type	B4147
Ordering code	B39841B4147U410
Marking and package	C61157-A7-A67
Packaging	F61074-V8168-Z000
Date codes	L_1126
S-parameters	B4147_NB.s2p B4147_WB.s2p
Soldering profile	S_6001
RoHS compatible	defined as compatible with the following documents: "DIRECTIVE 2002/95/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 27 January 2003 on the restriction of the use of certain hazardous substances in electrical and electronic equipment. 2005/618/EC from April 18th, 2005, amending Directive 2002/95/EC of the European Parliament and of the Council for the purposes of establishing the maximum concentration values for certain hazardous substances in electrical and electronic equipment."

For further information please contact your local EPCOS sales office or visit our webpage at www.epcos.com .

**Published by EPCOS AG
Surface Acoustic Wave Components Division
P.O. Box 80 17 09, 81617 Munich, GERMANY**

© EPCOS AG 2008. This brochure replaces the previous edition.

For questions on technology, prices and delivery please contact the Sales Offices of EPCOS AG or the international Representatives.

Due to technical requirements components may contain dangerous substances. For information on the type in question please also contact one of our Sales Offices.

Please read *cautions and warnings and important notes* at the end of this document.



Important notes

The following applies to all products named in this publication:

1. Some parts of this publication contain **statements about the suitability of our products for certain areas of application**. These statements are based on our knowledge of typical requirements that are often placed on our products in the areas of application concerned. We nevertheless expressly point out **that such statements cannot be regarded as binding statements about the suitability of our products for a particular customer application**. As a rule, EPCOS is either unfamiliar with individual customer applications or less familiar with them than the customers themselves. For these reasons, it is always ultimately incumbent on the customer to check and decide whether an EPCOS product with the properties described in the product specification is suitable for use in a particular customer application.
2. We also point out that **in individual cases, a malfunction of passive electronic components or failure before the end of their usual service life cannot be completely ruled out in the current state of the art, even if they are operated as specified**. In customer applications requiring a very high level of operational safety and especially in customer applications in which the malfunction or failure of a passive electronic component could endanger human life or health (e.g. in accident prevention or life-saving systems), it must therefore be ensured by means of suitable design of the customer application or other action taken by the customer (e.g. installation of protective circuitry or redundancy) that no injury or damage is sustained by third parties in the event of malfunction or failure of a passive electronic component.
3. **The warnings, cautions and product-specific notes must be observed.**
4. In order to satisfy certain technical requirements, **some of the products described in this publication may contain substances subject to restrictions in certain jurisdictions (e.g. because they are classed as "hazardous")**. Useful information on this will be found in our Material Data Sheets on the Internet (www.epcos.com/material). Should you have any more detailed questions, please contact our sales offices.
5. We constantly strive to improve our products. Consequently, **the products described in this publication may change from time to time**. The same is true of the corresponding product specifications. Please check therefore to what extent product descriptions and specifications contained in this publication are still applicable before or when you place an order. We also **reserve the right to discontinue production and delivery of products**. Consequently, we cannot guarantee that all products named in this publication will always be available. The aforementioned does not apply in the case of individual agreements deviating from the foregoing for customer-specific products.
6. Unless otherwise agreed in individual contracts, **all orders are subject to the current version of the "General Terms of Delivery for Products and Services in the Electrical Industry" published by the German Electrical and Electronics Industry Association (ZVEI)**.
7. The trade names EPCOS, BAOKE, Alu-X, CeraDiode, CSSP, DSSP, MiniBlue, MKK, MLSC, MotorCap, PCC, PhaseCap, PhaseMod, SIFERRIT, SIFI, SIKOREL, SilverCap, SIMDAD, SIMID, SineFormer, SIOV, SIP5D, SIP5K, ThermoFuse, WindCap are **trademarks registered or pending** in Europe and in other countries. Further information will be found on the Internet at www.epcos.com/trademarks.