


- △1 Substrate: 1.59mm ±0.18mm [0.0625" ±0.007"] FR4/G10 or equivalent high temp material. 17µm [1/2 oz.] Cu clad. SnPb plating.
- △2 Leads: material- BeCu Alloy 194; plating- 60/40 SnPb 3.80-10.16µm [150-400µ"].
- △3 Test points: material- Phosphor Bronze; plating- Sn over 1.27µm [50µ"]. Ni. Gold flash on contact end.

Description: Carrier Adaptor

2 piece pluggable adaptor, PLCC ZIF socket with test probe to surface mountable PLCC emulator foot.

Tolerances: diameters ±0.03mm [±0.001"], PCB perimeters ±0.13mm [±0.005"], PCB thicknesses ±0.18mm [±0.007"], pitches (from true position) ±0.08mm [±0.003"], all other tolerances ±0.13mm [±0.005"] unless stated otherwise. Materials and specifications are subject to change without notice.

 <p>© 1994 IRONWOOD ELECTRONICS, INC. PO BOX 21151 ST. PAUL, MN 55121 Tele: (651) 452-8100 www.ironwoodelectronics.com</p>	<p>CA-PLCC068-Z-J-T-01 Drawing</p>	<p>Status: Released</p>	<p>Scale: 2:1</p>	<p>Rev: D</p>
	<p>Drawing: M. Lund</p>	<p>Date: 8/16/94</p>		<p>Modified: 8/30/00</p>
<p>File: CA-PLCC068-Z-J-T-01 Dwg</p>				