


36-44GHz Multifunction (MFC) Down-Converter

GaAs Monolithic Microwave IC

Preliminary

Description


The CHR2297 is a multifunction chip (MFC) which integrates a LO buffer amplifier, an IF amplifier and a single cold FET mixer. It is usable for down-conversion. It is designed for a wide range of applications, from military to commercial communication systems. The backside of the chip is both RF and DC grounds. This helps to simplify the assembly process. The circuit is manufactured with a p-HEMT process, 0.25 μ m gate length, via holes through the substrate, air bridges and electron beam gate lithography. It is available in chip form.



Main Features

- Broadband performance : 36-44GHz RF
- 2.5dB conversion gain
- 0dBm LO input power
- +4dBm input power (1dB gain comp.)
- DC power consumption, 65mA @ 4V
- Chip size : 1.33 x 1.68 x 0.10 mm

Conversion Gain



Main Characteristics

T_{amb.} = 25°C

	Parameter	Min	Typ	Max	Unit
F _{RF}	RF frequency range	36		44	GHz
F _{LO}	LO frequency range	30		39	GHz
F _{IF}	IF frequency range	2		6	GHz
G _c	Conversion Gain		2.5		dB

ESD Protection : Electrostatic discharge sensitive device. Observe handling precautions !

Electrical Characteristics

Tamb = +25°C

Symbol	Parameter	Min	Typ	Max	Unit
F _{RF}	RF frequency range	36		44	GHz
F _{LO}	LO frequency range	30		39	GHz
F _{IF}	IF frequency range	2		6	GHz
G _c	Conversion Gain		2.5		dB
P _{LO}	LO Input power		0		dBm
LO_IF Lk	LO Leakage on IF (for P _{LO} =0dBm)		-28		dBm
LO_RF Lk	LO Leakage on RF (for P _{LO} =0dBm)		-22		dBm
RF_IF Lk	RF Leakage on IF (for P _{RF} =-5dBm)		-50		dBm
P1dB	Input power at 1dB gain compression		+4		dBm
LO Match	LO Matching (1)		2.0:1		
RF Match	RF Matching (1)		2.0:1		
IF Match	IF Matching		2.0:1		
Vd	Drain bias voltage (pads Vd1, Vd2)		4		V
Vg	Gate bias voltage (pad Vg)		-1		V
Id	Drain bias current		65		mA

(1) A wire bond of typically 0.1 to 0.15 nH will improve the input and output matching.

Absolute Maximum Ratings (1)

Tamb = +25°C

Symbol	Parameter	Values	Unit
Vd	Drain bias voltage	4.5	V
Id	Drain bias current	100	mA
P _{LO}	Maximum LO input power	5	dBm
Ta	Operating temperature range	-40 to +85	°C
Tstg	Storage temperature range	-55 to +125	°C


(1) Operation of device above any one of these parameters may cause permanent damage.

Typical on wafer measurement



Tamb: 25°C, Vd=4V, Vg= -1V, P_{LO}= 0dBm

Preliminary

Conversion gain versus RF frequency




Conversion gain versus RF input power




Preliminary


LO Leakage on RF port



LO Leakage on IF port




Recommended assembly plan



25µm wedge bonding is recommended

Mechanical data

Preliminary



Tol: ±35µm

Chip thickness: 100µm. All dimensions are in micrometers

Ordering Information

Chip form : CHR2297-98F/00

Information furnished is believed to be accurate and reliable. However **United Monolithic Semiconductors S.A.S.** assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of **United Monolithic Semiconductors S.A.S.** Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. **United Monolithic Semiconductors S.A.S.** products are not authorised for use as critical components in life support devices or systems without express written approval from **United Monolithic Semiconductors S.A.S.**