



Features


- ◇ For IF SAW filter
- ◇ High attenuation
- ◇ Single-ended operation
- ◇ Dual In-line Package
- ◇ RoHS compliant (2002/95/EC), Pb-free

Specifications


| Parameter | Unit | Minimum | Typical | Maximum |
|----------------------------------|----------------------------|---------|---------|---------|
| Center Frequency | MHz | 190.85 | 191 | 191.15 |
| Insertion Loss | dB | - | 28.4 | 30 |
| 1 dB Bandwidth | MHz | 16.3 | 16.43 | - |
| 3 dB Bandwidth | MHz | - | 16.72 | - |
| 50 dB Bandwidth | MHz | - | 17.8 | 18 |
| Passband Variation | dB | - | 0.8 | 1 |
| Absolute Delay | usec | - | 3.39 | - |
| Ultimate Rejection | dB | 50 | 52 | - |
| Material Temperature coefficient | KHz/°C | -3.44 | | |
| Substrate Material | - | 112LT | | |
| Ambient Temperature | °C | 25 | | |
| Operating Temperature Range | °C | -40 | - | +85 |
| Storage Temperature Range | °C | -45 | - | +105 |
| DC Voltage | V | 0 | | |
| Input Power | dBm | - | - | 10 |
| ESD Class | - | 1A | | |
| Package Size | DIP3512 (35.0x12.8x4.7mm3) | | | |

Notes:

1. All specifications are based on the test circuit shown;
2. In production, all specifications are measured by Agilent Network analyzer and full 2 port calibration at room temperature;
3. Electrical margin has been built into the design to account for the variations due to temperature drift and manufacturing tolerances;
4. This is the optimum impedance in order to achieve the performance show.

| | | | | |
|--|--|-------------|------------|------|
|  | SIPAT Co., Ltd. (CETC No.26 Research Institute) #14 Nanping Huayuan Road, Chongqing, China, 400060 | Part Number | LBT19101 | |
| | | Rev. Date | 2008-04-22 | |
| | | Ver. | 1.0 | Page |


Matching Configuration



L1=27nH L2=22nH
C1=C2=27pF
Source/Load Impedance=50 ohm

Notes - Component values may change depending
on board layout.

Package Dimension



Pad Configuration:

Input 1
Output 5
Ground All Others

Marking Configuration:

1) SIPAT: Manufacturer Name
2) LBT19101: Part Number
3) XXYYZZ: Date Code

Package: DIP3512

Unit: mm




SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

| | | |
|-------------|------------|----------|
| Part Number | LBT19101 | |
| Rev. Date | 2008-04-22 | |
| Ver. | 1.0 | Page 2/3 |




Typical Performance

Frequency Respond




Horizontal: 5MHz/Div Vertical: 10dB/Div

Passband Respond




Horizontal: 5MHz/Div Vertical: 0.5dB/Div

Group Delay Variation($f_0 \pm 8\text{MHz}$)




Horizontal: 5MHz/Div Vertical: 50ns/Div

Phase Linearity($f_0 \pm 8\text{MHz}$)




Horizontal: 5MHz/Div Vertical: 10deg/Div

Smith Chart S11



Smith Chart S22



SIPAT Co., Ltd.
(CETC No.26 Research Institute)
#14 Nanping Huayuan Road,
Chongqing, China, 400060

| | | |
|-------------|------------|----------|
| Part Number | LBT19101 | |
| Rev. Date | 2008-04-22 | |
| Ver. | 1.0 | Page 3/3 |