



SPECIFICATION FOR COTCO LED LAMP

Document No: SPE/LC512TWN1-25G-A1
Model No : LC512TWN1-25G-A1
Rev. No: 01
Date: 2005-05-19


Description:

25 Degree 5mm Round LED Lamp in White
Color with Water Transparent Lens and
Stopper

Dice Material: InGaN

Confirmed
by Customer: _____

Date: _____




Applications:

- Advertising Signs
- Indicators
- LCD Back Light
- Illuminations

Absolute Maximum Ratings at Ta = 25°C

Items	Symbol	Absolute maximum Rating	Unit
Forward Current	I _F	25	mA
Peak Forward Current*	I _{FP}	100	mA
Reverse Voltage	V _R	5	V
Power Dissipation	P _D	100	mW
Operation Temperature	T _{opr}	-40 ~ +95	°C
Storage Temperature	T _{stg}	-40 ~ +100	°C
Lead Soldering Temperature	T _{sol}	Max.260°C for 3 sec Max. (3mm from the base of the epoxy bulb)	

Dimension Drawing



*pulse width <=0.1msec duty <=1/10

Typical Electrical & Optical Characteristics (Ta = 25°C)

Items	Symbol	Condition	Min.	Typ.	Max.	Unit
Forward Voltage	V _F	I _F = 20mA	---	3.4	4.0	V
Forward Voltage	V _F	I _F = 1.0μA	1.7	---	2.5	V
Reverse Current	I _R	V _R = 5V	---	---	100	μA
Luminous Intensity	I _v	I _F = 20mA	4180	7200	---	mcd
Chromaticity Coordinates	x	I _F = 20mA	---	0.31	---	---
	y	I _F = 20mA	---	0.32	---	---
50% Power Angle	2θ _{1/2} H-H	I _F = 20mA	---	25	---	deg

Standard bins for LC512TWN1-25G-A1 (I_F = 20mA):

Lamps are sorted to Luminous Intensity –I_v, V_F & Chromaticity Coordinates –(X,Y) bins shown.

Orders for LC512TWN1-25G-A1 may be filled with any or all bins contained as below.

All Luminous Intensity –I_v, V_F & Chromaticity Coordinates –(X,Y) values shown and specified are at I_F =20mA.

* **X+**

		A1	A2	B1	B2	c			
Luminous Intensity (I _v)	12000mcd						Z		
	8200mcd								Y
	5860mcd								
	4180mcd								X

Chromaticity Coordinates (X,Y)

* X+ indicates Luminous Intensity is at X bin or above.

Rank		A1				A2				B1			
Chromaticity Coordinates	x	0.245	0.264	0.280	0.264	0.264	0.283	0.296	0.280	0.283	0.307	0.313	0.296
	y	0.229	0.267	0.248	0.220	0.267	0.305	0.276	0.248	0.305	0.337	0.297	0.276

Rank		B2				c			
Chromaticity Coordinates	x	0.307	0.330	0.330	0.313	0.330	0.361	0.356	0.330
	y	0.337	0.360	0.318	0.297	0.360	0.385	0.351	0.318


Forward Voltage (V_F)

Rank	V6	V7	V8	V9	V10	V11	V12
Voltage	2.6-2.8V	2.8-3.0V	3.0-3.2V	3.2-3.4V	3.4-3.6V	3.6-3.8V	3.8-4.0V

Important Notes:

- 1) All ranks will be included per delivery, rank ratio will be based on the Dices distribution.
- 2) Pb content <1000PPM.
- 3) Tolerance of measurement of luminous intensity is ±15%.
- 4) Tolerance of measurement of the Color Coordinates is ± 0.015.
- 5) Tolerance of measurement of Vf is ±0.05 V.
- 6) Packaging methods are available for selection, Please refer to PACKAGING STANDARD.
- 7) Please refer to LED LAMP RELIABILITY TEST STANDARD for reliability test conditions.
- 8) Please refer to APPLICATION NOTES for Application.

CIE Chromaticity Diagram



Graphs




FIG.1 FORWARD CURRENT VS. FORWARD VOLTAGE.




FIG.2 REVERSE CURRENT VS. REVERSE VOLTAGE.




FIG.3 RELATIVE LUMINOUS INTENSITY VS. FORWARD CURRENT




FIG.4 RELATIVE LUMINOUS INTENSITY VS. WAVELENGTH.




FIG.5 MAXIMUM FORWARD DC CURRENT VS AMBIENT TEMPERATURE ($T_{jmax}=105\text{ }^{\circ}\text{C}$)




FIG.6 FAR FIELD PATTERN

Items	Signatures	Date
Prepared by	LiuZM	2005-05-19
Checked by	HuangJD	2005-05-19
Approved by	David	2005-05-19
FCN#	FCN20050163	

Revision History		
Rev. No	Date	Change Description

Data is subject to change without prior notice; please refer to COTCO Website for the latest version.

Copyright©2002 Cotco International Ltd.