



UNCONTROLLED DOCUMENT



NOTES:



1. ANODE/CATHODE
2. CATHODE/ANODE
3. NO CONNECT
4. EMITTER
5. COLLECTOR
6. BASE

PART NUMBER  
OCP-PCTB126/X

REV. E.C.N. NUMBER AND REVISION COMMENTS DATE

CAUTION: STATIC SENSITIVE DEVICE  
FOLLOW PROPER E.S.D. HANDLING PROCEDURES  
WHEN WORKING WITH THIS PART.

PART= /X	CTR (%)
/A	60 TO 600
/B	60 TO 300



PARAMETER	SYMBOL	MAX	UNITS
I FORWARD CURRENT	I <sub>F</sub>	±50	mA
PEAK FORWARD CURRENT	I <sub>FM</sub>	±1	A
POWER DISSIPATION	P <sub>D</sub>	70	mW
0 COLLECTOR-EMITTER VOLTAGE	V <sub>CE0</sub>	60	V
EMITTER-COLLECTOR VOLTAGE	V <sub>EC0</sub>	6	V
COLLECTOR-BASE VOLTAGE	V <sub>CB0</sub>	60	V
EMITTER-BASE VOLTAGE	V <sub>EB0</sub>	6	V
COLLECTOR CURRENT	I <sub>C</sub>	50	mA
COLLECTOR POWER DISSIPATION	P <sub>C</sub>	150	mW
TOTAL POWER DISSIPATION	P <sub>TOT</sub>	200	mW
ISOLATION VOLTAGE 1 MIN.	V <sub>ISO</sub>	5000	V <sub>RMS</sub>
OPERATING TEMP.	T <sub>opr</sub>	-30 TO +100	°C
STORAGE TEMP.	T <sub>stg</sub>	-55 TO +125	°C
SOLDERING TEMP.	T <sub>sol</sub>	+260	°C
2.0mm FROM BODY		10 SEC. MAX	

ELECTRO-OPTICAL CHARACTERISTICS (T<sub>o</sub>=25°C)

PARAMETER	SYMBOL	CONDITIONS	MIN	TYP	MAX	UNITS
I FORWARD VOLTAGE	V <sub>F</sub>	I <sub>F</sub> =±20mA	-	1.2	1.4	V
PEAK FORWARD VOLTAGE	V <sub>FM</sub>	I <sub>FM</sub> =±0.5A	-	-	3.5	V
TERMINAL CAPACITANCE	C <sub>t</sub>	V=0, f=1kHz	-	30	-	pF
0 COLLECTOR DARK CURRENT	I <sub>CE0</sub>	V <sub>CE</sub> =20V, I <sub>F</sub> =0	-	-	10 <sup>-7</sup>	A
T CURRENT TRANSFER RATIO	CRT	I <sub>F</sub> =±1mA, V <sub>CE</sub> =5V	60	-	600	%
COLLECTOR-EMITTER SATURATION VOLTAGE	V <sub>CE(sat)</sub>	I <sub>F</sub> =±20mA, I <sub>C</sub> =1mA	-	0.1	0.3	V
ISOLATION RESISTANCE	R <sub>iso</sub>	DC500V	5x10 <sup>10</sup>	10 <sup>11</sup>	-	ohm
FLOATING CAPACITANCE	C <sub>f</sub>	V=0, f=1MHz	-	0.6	1.0	pF
CUT-OFF FREQUENCY	f <sub>c</sub>	V <sub>CE</sub> =5V, I <sub>C</sub> =2mA, R <sub>L</sub> =100ohm	-	80	-	kHz
RESPONSE TIME (RISE)	t <sub>r</sub>	V <sub>CE</sub> =2V, I <sub>C</sub> =2mA, R <sub>L</sub> =100ohm	-	5	20	μS
RESPONSE TIME (FALL)	t <sub>f</sub>	V <sub>CE</sub> =2V, I <sub>C</sub> =2mA, R <sub>L</sub> =100ohm	-	4	20	μS

I=INPUT, 0=OUTPUT, T=TRANSFER CHARACTERISTICS.

I=INPUT, 0=OUTPUT.

UNCONTROLLED DOCUMENT

\*UNLESS OTHERWISE SPECIFIED TOLERANCE IS ±0.25mm (±0.010")

REV. PART NUMBER  
OCP-PCTB126/X

CONFIDENTIAL INFORMATION  
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.



290 E. HELLEN ROAD  
PALATINE, ILLINOIS 60067  
PHONE: 1-847-359-2790  
WEB: HTTP://WWW.LUMEX.COM

SIX PIN DIP SINGLE CHANNEL PHOTOCOUPLER, BIPOLAR INPUT,  
TRANSISTOR OUTPUT WITH EXTERNAL BASE CONNECTION.

RELIABILITY NOTE  
OUR MANY YEARS OF EXPERIENCE DATA ACCUMULATION INDICATE THAT SOLDER HEAT IS A MAJOR CAUSE OF EARLY AND FUTURE FAILURE. PLEASE PAY ATTENTION TO YOUR SOLDERING PROCESS.

DRAWN BY: CK/DU CHECKED BY: APPROVED BY: DATE: 9-29-99  
PAGE: 1 OF 1  
SCALE: N/A