


120-001
Type A Series 72 Annular Convuluted Tubing
Thermally Stabilized Kynar®



**TYPE
 A**





TABLE I					
DASH NO.	A DIA		B DIA		MINIMUM BEND RADIUS
	MIN	MAX	MIN	MAX	
09	.24 (6.1)	.28 (7.1)	.38 (9.7)	.42 (10.7)	.75 (19.1)
12	.33 (8.4)	.37 (9.4)	.48 (12.2)	.52 (13.2)	1.00 (25.4)
16	.45 (11.4)	.50 (12.7)	.60 (15.2)	.66 (16.8)	1.38 (35.1)
20	.57 (14.5)	.62 (15.7)	.71 (18.0)	.77 (19.6)	1.69 (42.9)
24	.69 (17.5)	.75 (19.1)	.88 (22.4)	.94 (23.9)	1.88 (47.8)
28	.81 (20.6)	.87 (22.1)	1.00 (25.4)	1.08 (27.4)	2.00 (50.8)
32	.93 (23.6)	1.00 (25.4)	1.12 (28.4)	1.20 (30.5)	2.38 (60.5)
40	1.18 (30.0)	1.25 (31.8)	1.36 (34.5)	1.44 (36.6)	2.88 (73.2)

Metric dimensions (mm) are in parentheses.

Note: Tubing supplied in random lengths.
 For specific size lengths, consult factory.