

Product SKU: C2065.21.03

Product Description: Hook-Up Wire, UL 1007, UL 1569, CSA TR-64, Gauge Size (AWG): 16, Conductor/Strands: 26/30,

Jacket: Premium Grade PVC, Temperature Range: -20°C to +105°C - Red - 1000 Ft. Spool

Product Category: Electronics - Hook-Up Wire - UL 1007, UL 1569, CSA TR-64 - STRANDED CONDUCTORS - Red



Product Construction:

Conductor: • 24 thru 16 AWG

• Fully-annealed, tinned copper per ASTM B-33

• Solid or stranded

Insulation: • Color Code: See chart below

• Premium grade color-coded PVC

• Temperature range: $-20\hat{A}^{\circ}C$ to $+105\hat{A}^{\circ}C$

Product Specification:

Conductor Size (AWG): • 16

Conductor/Strands: • 26/30

No. of Pairs: • 1

Jacket Color: • Red

Nominal Insulation Thickness • 0.016 (in):

Nominal Insulation Thickness • 0.40 (mm):

Nominal Outside Diameter (in): • 0.092

Nominal Outside Diameter • 2.34 (mm):

Standard Packaging: • 1000' Spool

Standard Package Quantity:	• 1
UPC #:	• 079407767373
Put-up:	• 1000
SCC-14:	• 50079407767377
Cube:	• 277.0596
Weight Per Unit of Measure:	• .0106
ColorOption:	• Red
Product Information:	
Applications:	• Internal wiring of electrical and electronic equipment
	• Internal wiring of panels and meters
	Point-to-point wiring
	• Suggested voltage rating: 300 Volts
Compliances:	• CSA TR-64 - 90°C, 300V
	• Designed to Meet UL VW-1 Vertical Wire Flame Test
	• UL Style 1007 - 80°C, 300V
	• UL Style 1569 - 105°C, 300V
Packaging:	• 10,000 foot (3048m) Reels
	• 1000' (305m) Spools
	Other put-ups available- consult Customer Service
Reference Charts Color Code Chart	
Technical Specifications Unit Conversion Factors Cable Design Equations - Balanced Pair	

T

<u>U</u> <u>C</u>: **Insulation and Jacket Properties Temperature Conversion Chart Decimal and Unit Conversion Factors** Cable Design Equations - Braid Shield AWG Conductor Chart
Conduit Capacity Chart
Cable Design Equations

Cable Design Equations - Coaxial Cable

Engineering Prefixes

Coax Connector Cross Reference

Glossary





Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

