

Product Brief

CP2290 V1.1

Audio Power Amplifier Series

1.25W, Mono, Audio Power Amplifier

www.datasheet General Description

The CP2290 is an audio power amplifier designed for demanding audio applications. It is capable of delivering 1.25 watt of continuous average power to an 8Ω BTL load with less than 1% distortion (THD+N) from a 5V battery voltage. It operates from 2.2V to 5.5V.

5V battery voltage. It operates from 2.2V to 5.5V.

Features like excellent RF-rectification immunity, the space-saving CSP9 and MSOP8 packages, the advanced pop & click circuitry, a

The CP2290 is unity-gain stable, and the gain can be configured by external resistors.

minimal count of external components and low-power shutdown mode





Features

- 2.2V 5.5V operation
- Power output at 5.0V & 1% THD
 Power output at 3.6V & 1% THD
 Ultra low shutdown current
 1.25W (typ)
 0.6W (typ)
 0.01µA (typ)
- Improved pop & click circuitry eliminates noises during turn-on and turn-off transitions
- Thermal overload protection circuitry

make the CP2290 ideal for wireless handsets.

- No output coupling capacitors, bootstrap capacitors required
- Unity-gain stable
- External gain configuration capability
- Available in space-saving packages: CSP9 and MSOP8
- RoHS compliant and 100% lead(Pb)-free

Applications


- Wireless handsets
- Portable audio devices
- PDAs
- Notebook computers

Product Brief


1.25W, Mono, Audio Power Amplifier

www.datasheet-**Pin**nConfigurations

CSP9 Package (Top View)




CSP9 Marking




XY -Manufacture Date Code A8G - CP2290GITLX

MSOP8 Package (Top View)



MSOP8 Marking



XY -Manufacture Date Code A9G - CP2290GMM

1.25W, Mono, Audio Power Amplifier

Typical Application

www.datasheet4u.com 20kΩ R_f c_s 1μF VDD 20kΩ C_{i} R_{i} 0.1µF **CP2290** IN-Audio input VO+ IN+ $20k\Omega$ W **BYPASS** 20kΩ C_B 1µF VO-Bias $V_{DD}/2$ Circuitry SHUTDOWN V_{IH} V_{IL} **GND**

Contact with Chiphomer

4F, Building D, 1618 Yishan Road Shanghai, 201103, P.R.C.

Tel: (86)21-64014543 64058488

Fax: (86)21-64050030 Sale: sales@chiphomer.com

Technical support: support@chiphomer.com

Web site: www.chiphomer.com

Shenzhen Office:

10D, Building 2, Dushi Yangguang Garden CheGongMiao, Futian District, Shenzhen, 518048,

P.R.C.

Tel: (86)755-82046706 82047789

Fax: (86)755-8204670