FM1114

Nonvolatile 3V Quad State Saver

Features

Nonvolatile State Saver

- Logic States Retained in Absence of Power
- Outputs Automatically Restored at Power-up
- Unlimited Number of State Changes
- Max t_{PD} 50ns at 2.7V
- Max Frequency 1 MHz

Overview

The FM1114 is an innovative FRAM-based device that stores inputs like conventional logic and retains the stored state in the absence of power. This product solves three basic problems in an elegant fashion. First, it provides continuous access to nonvolatile system settings without performing a memory read operation or using dedicated processor I/O pins. Second, it allows the storage of signals that may change frequently and possibly without notice. Third, it allows the nonvolatile storage of a system setting without the system overhead and extra pins of a serial memory.

Functionally, the inputs are stored and passed to the output on the rising edge of the clock CLK. This unique product serves a variety of applications. Here are a few applications:

- Control relays or valves with automatic setting on power-up without processor intervention
- Interface to soft/momentary front-panel switch and indicator lamp. Capture switch settings and drive LEDs without processor intervention
- Replaces jumpers & control signal routing
- Initialize state of I/O card signals
- Eliminate the overhead of serial memory for systems needing only a bit of data




Low Power Operation

- Supply voltage of 2.7V to 3.6V
- 0.5 µA Standby Current

Industry Standard Configuration

- Industrial Temperature -40° C to +85° C
- 16-pin "Green"/RoHS QFN Package

Pin Configuration




| Top ' | View |
|-------|------|
|-------|------|

| Pin Names | Function |
|----------------|----------------|
| D _N | Data In |
| Q _N | Data Out |
| EN | Enable |
| CLK | Clock |
| VDD | Supply Voltage |
| VSS | Ground |

| Ordering Information | | | |
|----------------------|--|--|--|
| FM1114-QG | Quad State Saver, 16-pin "Green"/RoHS QFN | | |

This is a product in the pre-production phase of development. Device characterization is complete and Ramtron does not expect to change the specifications. Ramtron will issue a Product Change Notice if any specification changes are made. Rev. 2.0

Block Diagram and Truth Table



| INPUTS | | INPUTS O | |
|--------|--------|----------|-------|
| EN | CLK | Dn | Qn |
| Η | 1 | L | L |
| Н | 1 | Н | Н |
| Н | H or L | Х | Q_0 |
| L | Х | Х | Hi-Z |

L Low voltage level H High voltage level X Don't Care

 $\uparrow CLK rising edge$ $Q_0 Previous output state before CLK \uparrow$

Pin Descriptions

| Pin Name | I/O | Description |
|----------|--------|--|
| D(3:0) | Ι | Data inputs |
| Q(3:0) | 0 | Data outputs |
| CLK | Ι | Clock: On a rising edge of CLK, the D_N inputs are transferred to the Q_N outputs. While CLK is high or low, the Q_N outputs do not change regardless of the state of the data inputs. See truth table. |
| EN | Ι | Enable. This active-high input enables the device. When low, inputs are ignored and updates to the nonvolatile cells are prevented. When high, the device operates normally. Do not tie this pin to V_{DD} . |
| VDD | Supply | Power Supply (2.7V to 3.6V) |
| VSS | Supply | Ground |

Description

Nonvolatile storage applied to logic is a revolutionary concept. The FM1114 simplifies the design of system control functions. This product is unique because it remembers the stored output values in the absence of power. Any change in the latched state is automatically written to a nonvolatile ferroelectric latch. This function is possible due to the fast write time and extremely high write endurance of the underlying ferroelectric memory technology.

Use of Enable Pin

The FM1114 has an enable pin that is intended to be used in conjunction with a system reset. An active-low reset may be tied directly to the EN pin. At power-up, /RESET will be held low for some time during which the data input and CLK pins will be ignored. Once the system comes out of reset and EN goes high, the outputs Q_N drive to the state that were previously latched and the device operates normally. When the EN pin is low, the outputs Q_N are tristated.

The enable pin must not be tied to V_{DD} because the device does not have any power management circuits to monitor V_{DD} . The enable input must be held low during power cycles.

Electrical Specifications Absolute Maximum Ratings

| Symbol | Description | Ratings |
|-------------------|--|--------------------------------------|
| V _{DD} | Power Supply Voltage with respect to V _{SS} | -1.0V to +5.0V |
| V _{IN} | Voltage on any signal pin with respect to V_{SS} | -1.0V to +5.0V |
| | | and $V_{IN} < V_{DD} + 1.0V$ |
| T _{STG} | Storage temperature | -55° C to $+ 125^{\circ}$ C |
| T _{LEAD} | Lead temperature (Soldering, 10 seconds) | 300° C |
| V _{ESD} | Electrostatic Discharge Voltage | |
| | - Human Body Model (JEDEC Std JESD22-A114-B) | TBD |
| | - Charged Device Model (JEDEC Std JESD22-C101-A) | TBD |
| | - Machine Model (JEDEC Std JESD22-A115-A) | TBD |
| | Package Moisture Sensitivity Level | TBD |

Stresses above those listed under Absolute Maximum Ratings may cause permanent damage to the device. This is a stress rating only, and the functional operation of the device at these or any other conditions above those listed in the operational section of this specification is not implied. Exposure to absolute maximum ratings conditions for extended periods may affect device reliability.

| Symbol | Parameter | Min | Тур | Max | Units | Notes |
|------------------|--|---------------------|-----|----------------|-------|-------|
| V _{DD} | Power Supply Voltage | 2.7 | - | 3.6 | V | |
| I _{SB} | Standby Current | | - | 0.5 | μA | 1 |
| C _{PD} | Power Dissipation Capacitance | | - | 330 | pF | 2 |
| I _{LI} | Input Leakage Current | | | ±1 | μΑ | 3 |
| I _{LO} | Output Leakage Current | | | ±1 | μΑ | 3 |
| V _{IL} | Input Low Voltage | -0.3 | | $0.3 V_{DD}$ | V | |
| V _{IH} | Input High Voltage | 0.7 V _{DD} | | $V_{DD} + 0.3$ | V | |
| V _{OH} | Output High Voltage | | | | | |
| | $@ I_{OH} = -1 mA$ | $V_{DD} - 0.5$ | | - | V | |
| V _{OL} | Output Low Voltage | | | | | |
| | $@ I_{OL} = 1 \text{ mA} (V_{DD} = 2.7 \text{V})$ | - | | 0.4 | V | |
| | @ $I_{OL} = 10 \text{ mA} (V_{DD} = 2.7 \text{V})$ | - | | 0.8 | V | |
| V _{HYS} | Input Hysteresis (CLK, EN) | 200 | | | mV | 4 |

Notes

1. CLK = V_{SS} , all other inputs at V_{DD} or V_{SS} .

2. To calculate device power dissipation, $P_D = C_{PD} * V_{DD}^2 * f_i + C_L * V_{DD}^2 * f_o$, where f_i is the input clk freq, f_o is the output freq, and C_L is the output load capacitance. Active current I_{DD} may be calculated as $I_{DD} = C_{PD} * V_{DD} * f_i$, assuming outputs are floating.

3. V_{IN} or $V_{OUT} = V_{SS}$ to V_{DD} .

4. This parameter is characterized but not tested.

| AC Parameters (| $(T_A = -40^\circ \text{ C to} + 85^\circ$ | C, $V_{DD} = 2.7V$ to 3.6V, $C_L = 30$ | pF unless otherwise specified) |
|-----------------|--|--|--------------------------------|
|-----------------|--|--|--------------------------------|

| Symbol | Parameter | Min | Max | Units | Notes |
|-------------------|---|-----|-----|-------|-------|
| f _{MAX} | Maximum Clock Frequency | | 1 | MHz | |
| t _{LOW} | CLK Low Period | 0.3 | | μs | |
| t _{HIGH} | CLK High Period | 0.3 | | μs | |
| t _{PD} | Propagation delay CLK to Q _N | | 50 | ns | |
| t _{HZ} | EN Low to Q _N Hi-Z | | 25 | ns | 1 |
| t _R | Input Rise Time | | 100 | ns | 1 |
| t _F | Input Fall Time | | 100 | ns | 1 |
| t _{DS} | Data (D_N) Setup Time to CLK \uparrow | 5 | | ns | |
| t _{DH} | Data (D _N) Hold Time after CLK \uparrow | 10 | | ns | |
| t _{EHD} | EN Hold Time (EN High after CLK ↑) | 50 | - | ns | |
| $t_{\rm EH}$ | EN High Time | 5 | | μs | |
| $t_{\rm EL}$ | EN Low Time | 2 | | μs | |

Notes

1. This parameter is characterized but not tested.

Power Cycling and Data Retention ($T_A = -40^\circ$ C to $+ 85^\circ$ C, $V_{DD} = 2.7$ V to 3.6V, unless otherwise specified)

| Symbol | Parameter | Min | Max | Units | Notes |
|-------------------|---|-----|-----|-------|-------|
| | Nonvolatile Data Retention Time | 45 | - | years | |
| t _{VDR} | V _{DD} Rise Time | 0.1 | - | μs/V | 1 |
| t _{VDF} | V _{DD} Fall Time | 0.1 | - | μs/V | 1 |
| t _{RES} | EN High to Q _N Restore Time | - | 0.5 | μs | 2 |
| t _{PDS} | EN Low to Power Down Time | 1 | - | μs | |
| t _{EHFC} | EN High to First Clock (CLK ↑) after Power Up | 4 | - | μs | 3 |

Notes

1. Slope measured at any point on V_{DD} waveform.

2. After power up, when EN goes high the nonvolatile latches are read and the values restored to the outputs Q_N.

3. After power up, this is the minimum time required before a state change operation may occur. EN and V_{DD} may be coincident at power up, and in this case t_{EHFC} time is referenced to V_{DD} (min) and CLK \uparrow .

Capacitance ($T_A = 25^\circ C$, f=1.0 MHz, $V_{DD} = 3.3V$)

| Symbol | Parameter | Min | Max | Units | Notes |
|--------|-------------------|-----|-----|-------|-------|
| CI | Input Capacitance | - | 14 | pF | 1 |


Notes

1. This parameter is characterized but not tested.


AC Test Conditions

| Input Pulse Levels | 0.1 V_{DD} to 0.9 V_{DD} |
|--------------------------------|------------------------------|
| Input Rise and Fall Times | 10 ns |
| Input and Output Timing Levels | $0.5 V_{DD}$ |
| Output Load Capacitance | 30pF |

FM1114 Signal Timing




Power Cycle Timing




Mechanical Drawing

16-pin QFN (4.0mm x 4.0mm body, 0.65mm pitch)



Note: All dimensions in <u>millimeters</u>. Care must be taken to ensure PCB traces and vias are not placed within the exposed metal pad area.



Revision History

| Revision | Date | Summary |
|----------|-----------|--|
| 1.0 | 8/8/2007 | Initial Release. |
| 1.1 | 8/22/2007 | Reduced I _{SB} spec. |
| 2.0 | 2/20/2008 | Changed to Pre-Production status. Changed V_{HYS} and t_{EHD} (min.) limits. |