

# GAE GREAT AMERICAN ELECTROINCS

## 2N6203

Silicon NPN power UHF transistor 2N6203 is designed primarily for communications transceiver equipment (Class C). Also used for auto-oscillator and frequency multiplier circuits.

Output Power: 12 Watt  
 Frequency Range: 100-400 Mhz  
 Voltage: 28 V  
 Package Type: MT-72  
 Common Emitter Configuration  
 Emitter Ballasting  
 Aluminum Metalization

### Electrical Characteristics ( $T_{CASE}=40^{\circ}C$ )

SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
$P_{out}$	$f_o = 400 \text{ Mhz}/V_{cc}=28V/P_{IN}=3W$	12			W
$G_p$	$f_o = 400 \text{ Mhz}/V_{cc}=28V/P_{out}=12W$	6			dB
$\lambda_c$	$f_o = 400 \text{ Mhz}/V_{cc}=28V/P_{out}=12W$	50	70		%

### ABSOLUTE MAXIMUM RATINGS ( $T_{CASE} = 25^{\circ}C$ )

SYMBOL	PARAMETERS	VALUE	UNIT
$V_{CER}$	Collector-Emitter Voltage $R_{EB} \leq 100 \Omega$	60	V
$V_{EBO}$	Emitter-Base Voltage	4	V
$I_c$	Continuous Collector Current	1	A
$P_C$	Collector Power Dissipation	15*	W
$T_j$	Junction Temperature	160	$^{\circ}C$
$R_{th(j-c)}$	Junction-Case Thermal Resistance	8.8	$^{\circ}C/W$

\*For Dynamic Operation,  $T_{CASE} = 28^{\circ}C$