

The tolerance unless classified ± 0.3mm

MECHANICAL SPECIFICATION							
Overall Size	98.16 x 32.50	Module	H2 / H1				
View Area	93.5 x 15.8	W /O B/L	4.1 / 5.5				
Dot Size	0.60 x 0.65	EL B/L	_				
Dot Pitch	0.65 x 0.70	LED B/L	_				

PIN ASSIGNMENT						
Pin no.	Symbol Function					
1	Vss	Power supply(GND)				
2	Vdd	Power supply(+)				
3	Vo	Contrast Adjust				
4	RS	Register select signal				
5	R/W	Data read / write				
6	E	Enable signal				
7	DB0	Data bus line				
8	DB1	Data bus line				
9	DB2	Data bus line				
10	DB3	Data bus line				
11	DB4	Data bus line				
12	DB5	Data bus line				
13	DB6	Data bus line				
14	DB7	Data bus line				

ABSOLUTE MAXIMUM RATING											
ltem	Symbol		Condition		Min.			Max.		Units	
Supply for logic voltage	Vdd-Vss		25°0	°C -		0.3		7		V	~
LCD driving supply voltage	Vdd-Vee		25°C	25°C -(-0.3		9		V	\mathbf{D}
Input voltage	Vin		25°0	C -(0.3 🛛		Vdd+0.3		V	
ELEC	TRICA	LC	CHARA	AC7	ĒŔ	rist	ric.	S)	
Item	Symbol	Сс	ndition	N	1in.	Тур	ical	IV	lax.	Units	
Power supply voltage	Vdd-Vss	25 ⁰ C		2.	2.7 –		- 0	5.5		V	
LCD operation voltage	Vop		Тор	Ν	W	N	W	Ν	W	V	
		-20 ⁰ C		_	8.2	3	8.3	-	7.3	V	
			0°C	4.5	.7	4.8	Ι	5.1	-	V	
			25 ⁰ C	4.1	7.7	4.4	7.9	4.7	6.9	V	
			50°C	3.8	_	4.1		4.4	-	V	
			70 ⁰ C	_	6.7	-	6.9	-	6.2	V	
LCM current consumption (No B/L)	ldd	Vdd=5V		-	- 2		2	3		mA	
De al-liebt average a successfiere	LED/edge	e VB/L=4.2V		-		_		_		mA	
Backlight current consumption	LED/array	VB/L=4.2V		_		_		_		mA	

47