



# MI-200<sup>TM</sup>

## Military COTS DC-DC Converters 50 to 100 W

### Features

- ✦ Inputs:
  - 28 Vdc per MIL-STD-704D/E
  - 155 Vdc per MIL-STD-1399A
  - 270 Vdc per MIL-STD-704D/E
- ✦ Single output: 2 – 48 Vdc
- ✦ Up to 23 W/in<sup>3</sup>
- ✦ MIL-STD-810 environments
- ✦ Up to 90% efficiency
- ✦ Remote sense
- ✦ Current limit
- ✦ OVP and thermal shut down
- ✦ Power boosters for higher power outputs
- ✦ ZVS/ZCS power architecture
- ✦ Low noise FM control
- ✦ Size: 4.6" x 2.4" x 0.5"  
(116.8 x 61.0 x 12.7 mm)

### Product Highlights

The MI-Series is designed for applications utilizing distributed power architecture based on Vicor's 1st Generation family of zero-current/zero-voltage switching, component level DC-DC converters. Operating at frequencies in excess of 1 MHz, the MI-Series offers state-of-the-art performance in terms of power density, efficiency, noise, ease of use, and reliability.

All units are manufactured in ISO 9001-registered facilities. Fully encapsulated in Vicor's industry standard package enables the MI-Series to meet MIL-STD-810 environmental requirements for humidity, fungus, salt, fog, explosive atmosphere, acceleration, vibration, and shock. (See page 32.)

Standard features such as wide output trimming/programming, current limiting, remote sense, output inhibit, and latching OVP and OTP combine to offer a high degree of protection, versatility, and reliability for power systems.

### Converter/Booster Specifications

(At  $T_{BP} = 25^{\circ}\text{C}$ , nominal line and 75% load, unless otherwise specified)

PARAMETER	MIN	TYP	MAX	UNITS	TEST CONDITIONS
<b>Input Characteristics</b>					
Input voltage range	See input voltage chart				
No load power dissipation	1.35		2.0	Watts	
<b>Output Characteristics</b>					
Set point accuracy		0.5	1.0	% Vnom	
Load/line regulation		0.05	0.2	% Vnom	LL to HL, 10% to FL
		0.2	0.5	% Vnom	LL to HL, NL to 10%
Output temperature drift		0.01	0.02	%/°C	
Output noise - pp		1.0	1.5	% Vnom	} Whichever is greater 20 MHz BW
		100	150	mV	
Output voltage trimming <sup>(1)</sup>	50		110	% Vnom	
Remote sense compensation		0.5		Vdc	
OVP set point <sup>(2)</sup>	115	125	135	% Vnom	Latching
Current limit	105		125	% Inom	Auto restart
Short circuit current <sup>(3)</sup>	20		130	% Inom	
<b>Control Pin Characteristics</b>					
Gate in high threshold		6		Vdc	
Gate in low threshold	0.65			Vdc	
Gate In low current			6	mA	
Power sharing accuracy	0.95		1.05		
<b>Isolation Characteristics</b>					
Isolation (input to output)	3,000			Vrms	
Isolation (output to baseplate)	500			Vrms	
Isolation (input to baseplate)	1,500			Vrms	
Input/output capacitance		50	75	pF	
<b>Environmental (MIL-STD-810)</b>					
Altitude - method 500.2	70,000			feet	Procedure II
Humidity - method 507.2	86/240			%/hours	Procedure 1, cycle 1
Acceleration - method 513.3	9			g's	Procedure 2
Vibration - method 514.3	20			g's	Procedure 1, category 6
Shock - method 516.3	40			g's	Procedure 1
<b>Reliability (MIL-HDBK-217F)</b>					
25°C Ground Benign: G.B.		2,478,477		hours	
50°C Naval Sheltered: N.S.		584,920		hours	
65°C Airborne Inhabited Cargo: A.I.C.		483,303		hours	
<b>Thermal Characteristics</b>					
Efficiency		80-90		%	
Baseplate to sink		0.07		°C/W	With thermal pads
Thermal shut down	90	95	105	°C	Latching
Baseplate operating temperature			+85	°C	See product grade
Storage temperature			+100	°C	See product grade
<b>Mechanical Specifications</b>					
Weight		6.0 (170)		ounces (grams)	

<sup>(1)</sup> 10 V, 12 V, and 15 V outputs, standard trim range  $\pm 10\%$ . Consult factory for wider trim range.

<sup>(2)</sup> No over temperature or voltage protection in booster modules.

<sup>(3)</sup> Output voltages of 5 V or less incorporate foldback current limiting; outputs of 10 V and above provide constant current limiting.

# Configuration Chart

## MI-2



Semi-custom driver and booster modules available: *Consult factory.*

(1) 16 V operation at 75% load.

(2) These units rated at 75% load from 125-150 Vin:

- MI-26Z-xV
- MI-26Y-xV
- MI-260-xW

28 Vdc input per MIL-STD 704D/E  
 155 Vdc input per DOD-STD-1399A  
 270 Vdc input per MIL-STD-704D/E

Input Voltage		
Nominal	Range	Transient
2 = 28 V	18 - 50 V <sup>(1)</sup>	60 V
5 = 155 V	100 - 210 V	230 V
6 = 270 V	125 - 400 V <sup>(2)</sup>	475 V
7 = 165 V	100 - 310 V	

Output Voltage		
Z = 2 V	T = 6.5 V	N = 18.5 V
Y = 3.3 V	R = 7.5 V	3 = 24 V
0 = 5 V	M = 10 V	L = 28 V
X = 5.2 V	1 = 12 V	J = 36 V
W = 5.5 V	P = 13.8 V	K = 40 V
V = 5.8 V	2 = 15 V	4 = 48 V

Product Grade	Operating Temp.
I	= -40°C to +85°C
M	= -55°C to +85°C

Output Power/Current	
	≥ 5 V < 5 V
Y =	50 W 10 A
X =	75 W 15 A
W =	100 W 20 A
V =	— 30 A

For additional power, 100 W and 75 W booster modules available. Change MI-2xx-xx to MI-Bxx-xx.

# Product Grade Specifications

PARAMETER	PRODUCT GRADE	
	I-Grade	M-Grade
Storage temperature	-55°C to +100°C	-65°C to +100°C
Operating temperature (baseplate)	-40°C to +85°C	-55°C to +85°C
Power cycling burn-in	12 hours, 25 cycles	96 hours, 200 cycles
Temperature cycled with power off	12 cycles	12 cycles
17°C per minute rate of change	-65°C to +100°C	-65°C to +100°C
Test data supplied at these temperatures*	-40°C, +80°C	-55°C, +80°C
Warranty	2 years	2 years
Environmental compliance	MIL-STD-810	MIL-STD-810
Derating	NAVMAT P-4855-1A	NAVMAT P-4855-1A

\*Test data available for review or download from vicorpower.com

# Mechanical Drawing

## MI-200 Mechanical Drawing

