



## UT60N03

Power MOSFET

### 30V, 60A N-CHANNEL LOGIC LEVEL MOSFET

#### DESCRIPTION



This device employs advanced MOSFET technology and features low gate charge while maintaining low on-resistance.

Optimized for switching applications, this device improves the overall efficiency of DC/DC converters and allows operation to higher switching frequencies.

#### FEATURES

- \*  $R_{DS(ON)} = 14m\Omega @ V_{GS} = 10V$
- \*  $R_{DS(ON)} = 24m\Omega @ V_{GS} = 4.5V$
- \* Low Capacitance
- \* Low Gate Charge
- \* Fast Switching Capability
- \* Avalanche Energy Specified

#### SYMBOL



#### ORDERING INFORMATION

| Ordering Number |                | Package | Pin Assignment |   |   | Packing   |
|-----------------|----------------|---------|----------------|---|---|-----------|
| Lead Free       | Halogen Free   |         | 1              | 2 | 3 |           |
| UT60N03L-TA3-T  | UT60N03G-TA3-T | TO-220  | G              | D | S | Tube      |
| UT60N03L-TM3-T  | UT60N03G-TM3-T | TO-251  | G              | D | S | Tube      |
| UT60N03L-TN3-R  | UT60N03G-TN3-R | TO-252  | G              | D | S | Tape Reel |
| UT60N03L-TN3-T  | UT60N03G-TN3-T | TO-252  | G              | D | S | Tube      |

|  |  |
|--|--|
| <p>UT60N03L-TA3-R</p> <p>(1) Packing Type</p> <p>(2) Package Type</p> <p>(3) Lead Free</p> | <p>(1) R: Tape Reel, T: Tube</p> <p>(2) TA3: TO-220, TM3: TO-251, TN3: TO-252</p> <p>(3) G: Halogen Free, L: Lead Free</p> |
|--|--|

■ ABSOLUTE MAXIMUM RATINGS (T<sub>c</sub>=25°C, unless otherwise specified)

| PARAMETER                                       |               | SYMBOL           | RATINGS    | UNIT |
|---|---------------|------------------|------------|------|
| Drain-Source Voltage                            |               | V <sub>DSS</sub> | 30         | V    |
| Gate-Source Voltage                             |               | V <sub>GSS</sub> | ±20        | V    |
| Continuous Drain Current (V <sub>GS</sub> =10V) |               | I <sub>D</sub>   | 60         | A    |
| Power Dissipation                               | TO-220        | P <sub>D</sub>   | 60         | W    |
|   | TO-251/TO-252 |                  | 45         |      |
| Derate above 25°C                               | TO-220        |                  | 0.4        | W/°C |
|   | TO-251/TO-252 |                  | 0.37       |      |
| Junction Temperature                            |               | T <sub>J</sub>   | +150       | °C   |
| Storage Temperature                             |               | T <sub>STG</sub> | -55 ~ +150 | °C   |

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.






■ THERMAL DATA

| PARAMETER           |               | SYMBOL          | RATINGS | UNIT |
|---------------------|---------------|-----------------|---------|------|
| Junction to Ambient | TO-220        | θ <sub>JA</sub> | 62.5    | °C/W |
|                     | TO-251/TO-252 |                 | 100     |      |
| Junction to Case    | TO-220        | θ <sub>JC</sub> | 2.5     | °C/W |
|                     | TO-251/TO-252 |                 | 2.73    |      |

■ ELECTRICAL CHARACTERISTICS (T<sub>c</sub>=25°C, unless otherwise specified)

| PARAMETER  | SYMBOL              | TEST CONDITIONS  | MIN   | TYP | MAX  | UNIT |    |
|--|---------------------|--|---|-----|------|------|----|
| <b>OFF CHARACTERISTICS</b>                             |                     |  |   |     |      |      |    |
| Drain-Source Breakdown Voltage                         | BV <sub>DSS</sub>   | V <sub>GS</sub> =0V, I <sub>D</sub> =250μA   | 30  |     |      | V    |    |
| Drain-Source Leakage Current                           | I <sub>DSS</sub>    | V <sub>DS</sub> =25V, V <sub>GS</sub> =0V  |   |     | 1    | μA   |    |
| Gate-Source Leakage Current                            | I <sub>GSS</sub>    | V <sub>DS</sub> =0V, V <sub>GS</sub> =±20V   |   |     | ±100 | nA   |    |
| <b>ON CHARACTERISTICS</b>                              |                     |  |   |     |      |      |    |
| Gate Threshold Voltage                                 | V <sub>GS(TH)</sub> | V <sub>DS</sub> =V <sub>GS</sub> , I <sub>D</sub> =250μA                                 | 1   |     | 3    | V    |    |
| Static Drain-Source On-Resistance                      | R <sub>DS(ON)</sub> | V <sub>GS</sub> =10V, I <sub>D</sub> =30A  |   | 14  | 23   | mΩ   |    |
|  |                     | V <sub>GS</sub> =4.5V, I <sub>D</sub> =19A   |   | 24  | 30   |      |    |
| <b>DYNAMIC PARAMETERS</b>                              |                     |  |   |     |      |      |    |
| Input Capacitance                                      | C <sub>ISS</sub>    | V <sub>DS</sub> =15V, V <sub>GS</sub> =0V, f=1MHz  |   | 900 |      | pF   |    |
| Output Capacitance                                     | C <sub>OSS</sub>    |  |   | 210 |      | pF   |    |
| Reverse Transfer Capacitance                           | C <sub>RSS</sub>    |  |   | 90  |      | pF   |    |
| <b>SWITCHING PARAMETERS</b>                            |                     |  |   |     |      |      |    |
| Turn-ON Time   | t <sub>(ON)</sub>   | V <sub>DD</sub> =15V, I <sub>D</sub> =7.9A, R <sub>L</sub> =18Ω, V <sub>GS</sub> =4.5V   |   |     | 90   | ns   |    |
| Turn-ON Delay Time                                     | t <sub>D(ON)</sub>  |  |   | 11  |      | ns   |    |
| Turn-ON Rise Time                                      | t <sub>R</sub>      |  |   | 49  |      | ns   |    |
| Turn-OFF Time  | t <sub>(OFF)</sub>  |  |   |     | 83   | ns   |    |
| Turn-OFF Delay Time                                    | t <sub>D(OFF)</sub> |  |   | 27  |      | ns   |    |
| Turn-OFF Fall-Time                                     | t <sub>F</sub>      |  |   | 28  |      | ns   |    |
| Turn-ON Time   | t <sub>(ON)</sub>   | V <sub>DD</sub> =15V, I <sub>D</sub> =7.9A, R <sub>L</sub> =18Ω, V <sub>GS</sub> =10V    |   |     | 48   | ns   |    |
| Turn-ON Delay Time                                     | t <sub>D(ON)</sub>  |  |   | 6   |      | ns   |    |
| Turn-ON Rise Time                                      | t <sub>R</sub>      |  |   | 26  |      | ns   |    |
| Turn-OFF Time  | t <sub>(OFF)</sub>  |  |   |     | 120  | ns   |    |
| Turn-OFF Delay Time                                    | t <sub>D(OFF)</sub> |  |   | 52  |      | ns   |    |
| Turn-OFF Fall-Time                                     | t <sub>F</sub>      |  |   | 28  |      | ns   |    |
| Total Gate Charge                                      | 5V                  | Q <sub>G</sub>   | V <sub>GS</sub> =0V~5V, V <sub>DD</sub> =15V, I <sub>D</sub> =19A, I <sub>G</sub> =1.0mA  |     | 18   | 28   | nC |
|  | 10V                 |  | V <sub>GS</sub> =0V~10V, V <sub>DD</sub> =15V, I <sub>D</sub> =19A, I <sub>G</sub> =1.0mA |     | 9.6  | 14   |    |
| Threshold Gate Charge                                  | Q <sub>G(TH)</sub>  | V <sub>GS</sub> =0V~1V, V <sub>DD</sub> =15V, I <sub>D</sub> =19A, I <sub>G</sub> =1.0mA |   | 1.0 | 1.5  | nC   |    |
| Gate-Source Charge                                     | Q <sub>GS</sub>     | V <sub>DD</sub> =15V, I <sub>D</sub> =19A, I <sub>G</sub> =1.0mA                         |   | 3.4 |      | nC   |    |
| Gate-Drain Charge                                      | Q <sub>GD</sub>     |  |   | 3.4 |      | nC   |    |
| <b>SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS</b> |                     |  |   |     |      |      |    |
| Drain-Source Diode Forward Voltage                     | V <sub>SD</sub>     | I <sub>SD</sub> =19A   |   |     | 1.25 | V    |    |
|  |                     | I <sub>SD</sub> =10A   |   |     | 1.0  |      |    |
| Reverse Recovery Time                                  | t <sub>rr</sub>     | I <sub>SD</sub> =9A, di <sub>s</sub> /dt =100A/s,  |   |     | 58   | ns   |    |
| Reverse Recovery Charge                                | Q <sub>RR</sub>     |  |   |     | 70   | nC   |    |

## TYPICAL CHARACTERISTICS



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.