

VCO Product Specification

 Model:
 VCO190-450T(Y)
 Rev:
 Date:
 8/31/2006

 Customer:
 SIRENZA MICRODEVICES, INC.

Operating Temperature Range: (-35 ° to 85 ° C)

Pb RoHS Compliant

To order models as RoHS Compliant add "Y" suffix to base model number.

Parameter	Min	Тур	Max	Units	X	Remarks
Frequency Range -	442	450	458	MHz	Х	
Tuning Voltage:						
442 MHz	0.5	1.3	i	Vdc	Х	
458 MHz		3.7	4.5	Vdc	Х	
Tuning Sensitivity -	6	7.5	9	MHz/V	Х	
Output Power -	-1	2	5	dBm	Х	
Output Phase Noise:						
10 kHz		-118	-112	dBc/Hz		
100 kHz		-138	-132	dBc/Hz	Х	
Power Supply -	4.75	5	5.25	Volts		
Supply Current -		10	14	mA	Х	
larmonic Suppression:						
2nd Harmonic		-15	-10	dBc	Х	
3rd Harmonic		-15	-10	dBc	Х	
Spurious (Non-Harmonic) -			-80	dBc		
Frequency Pushing - 4.75-5.25 V		0.1	1	MHz p-p		
Frequency Pulling - 12 dB RL		0.2	1	MHz p-p		
Funing Port Capacitance -		220		рF		
Output Impedance -		50		Ω		

Package Information

Package Type: T (0.5 x 0.5 x 0.156 inches)	Drawing Number:	60035
--	-----------------	-------

Comments

X Indicates parameter to be tested 100% in production

Performance tests and ratings for Sirenza Microdevices' products were performed internally by Sirenza and measured using specific computer systems and/or components and reflect the approximate performance of the the products as measured by those tests. Any difference in circuit implementation, test software, or test equipment may affect actual performance. The information provided herein is believed to be reliable at press time and Sirenza Microdevices assumes no responsibility for the use of this information. All such use shall be entirely at the user's own risk. Prices and specifications for Sirenza's limited warranty with regard to its products. These products may be patented or include patented technology. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. Sirenza Microdevices does not authorize or warrant any product for use in life-support devices and/or systems.

Page 1 of 1

Sirenza Microdevices, Inc.