

Part Number: C1703

Revision Level: 11/19/2012

**4C 14AWG 41/30BC PP, PVC****COMMAND® SERIES****A. CONSTRUCTION**

Conductor: 14 AWG 41/30 BC  
Insulation: .009" Wall, Polypropylene (PP)  
Cable Core: 4C @ 6.00" LHL  
Jacket: .030" Polyvinyl Chloride (PVC)  
Print Legend:

**CAROL® -- C1703 -- 4C 14AWG COMMAND SERIES AUDIO CABLE (UL) E60233-8  
CL3 60C -- CSA LL69381 AWM I/II A/B 80C 600V FT4 -- ROHS -- MADE IN USA  
(Date code) (Seq Footage)**

**DIAMETERS**

.071" nom  
.089" nom  
.215" nom  
.275" nom

**B. INDUSTRY APPROVALS**

National Electrical Code	Article 725
UL Standard 444	Type CL3
CSA International	Type AWM I/II A/B

**C. ELECTRICAL PROPERTIES**

Temperature: -20°C to +80°C  
Suggested Working Voltage: 600V Max  
Conductor DCR: 2.56 Ohms/M' @ 20°C (nom)  
Mutual Capacitance: 23.3 pF/ft @ 1kHz (nom)

**D. COLOR CODE**

Item	COLOR
1	BLACK
2	RED
3	WHITE
4	GREEN

**E. CUSTOMER APPROVAL**

Signature: \_\_\_\_\_  
Date: \_\_\_\_\_