

Part Number: C0520A

Revision Level: 0

Date: 10/25/2007

7 PR 24 7/32 TC FMPP OAS PVC

Computer Cable

A. CONSTRUCTION

Conductor:	#24 AWG 7/32 Tinned Copper	0.024" nom.
Insulation:	0.016" Wall Foamed Polypropylene	0.056" nom.
Pairing	2 conductors @ 2.00" LHL	0.111" nom.
Cable:	7P with AL / PE & # 24 7/32 TC DW	
Braid	# 36 AWG Tinned Copper 65% Min. Coverage	0.306" nom.
Jacket:	0.032" Wall Polyvinyl Chloride - Gray	0.370" +/- 0.019"
Print Legend:	<i>CAROL (R) 24 AWG -- C0520A -- 75C E111240-8 CM (UL) C (UL) CMH OR 80C AWM STYLE 2919 30V LOW VOLTAGE COMPUTER CABLE --- MADE IN USA (DATE CODE) (PRINT</i>	

DIAMETERS

B. INDUSTRY APPROVALS

National Electrical Code	Article 800
UL Standard 444	Type CM(UL)c(UL) CMH
UL Subject 758	AWM Style 2919

C. ELECTRICAL PROPERTIES

TEMPERATURE:	80C
SUGGESTED WORKING VOLTAGE (V _{rms}):	30V
CONDUCTOR D.C. RESISTANCE:	25.7 Ohms/1000 ft nom
SHIELD RESISTANCE:	3.5 Ohms/1000 ft nom
MUTUAL CAPACITANCE:	9.24 pF/ft @ 1kHz nom
GROUND CAPACITANCE:	16.63 pF/ft @ 1kHz nom
CHARACTERISTIC IMPEDANCE:	141.2 Ohms @ 1MHz nom

D. COLOR CODE (Listed as Individual Conductors or Pairs of Conductors)

1	Wht/Blu – Blu/Wht
2	Wht/Org – Org/Wht
3	Wht/Grn – Grn/Wht
4	Wht/Brn – Brn/Wht
5	Wht/Gry -- Brn/Wht
6	Red/Blu -- Blu/Red
7	Red/Org -- Org/Red