


塑封超快速整流二极管
反向电压 50 --- 400 V
正向电流 1.0 A

Plastic Ultra-Fast Recover Rectifiers
Reverse Voltage 50 to 400V
Forward Current 1.0A



特征 Features

- 反向漏电流低 Low reverse leakage
- 正向浪涌承受能力较强 High forward surge capability
- 高温焊接保证 High temperature soldering guaranteed:
260°C/10 秒, 0.375" (9.5mm)引线长度。
260°C/10 seconds, 0.375" (9.5mm) lead length,
- 引线可承受5 磅 (2.3kg) 拉力。 5 lbs. (2.3kg) tension
- 引线 and 管体皆符合RoHS标准。
Lead and body according with RoHS standard

机械数据 Mechanical Data

- 端子: 镀锡轴向引线 Terminals: Plated axial leads
- 极性: 色环端为负极 Polarity: Color band denotes cathode end
- 安装位置: 任意 Mounting Position: Any

极限值和温度特性 TA = 25°C 除非另有规定。

Maximum Ratings & Thermal Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	EGP 10A	EGP 10B	EGP 10C	EGP 10D	EGP 10F	EGP 10G	单位 Unit
最大可重复峰值反向电压 Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	300	400	V
最大均方根电压 Maximum RMS voltage	V _{RMS}	35	70	105	140	210	280	V
最大直流阻断电压 Maximum DC blocking voltage	V _{DC}	50	100	150	200	300	400	V
最大正向平均整流电流 Maximum average forward rectified current	I _{F(AV)}	1.0						A
峰值正向浪涌电流 8.3ms单一正弦半波 Peak forward surge current 8.3 ms single half sine-wave	I _{FSM}	30						A
典型热阻 Typical thermal resistance	R _{θJA}	65						°C/W
工作结温和存储温度 Operating junction and storage temperature range	T _j , T _{STG}	-55 --- +150						°C

电特性 TA = 25°C 除非另有规定。


Electrical Characteristics Ratings at 25°C ambient temperature unless otherwise specified.

	符号 Symbols	EGP 10A	EGP 10B	EGP 10C	EGP 10D	EGP 10F	EGP 10G	单位 Unit
最大正向电压 Maximum forward voltage I _F = 1.0A	V _F	0.95				1.25		V
最大反向电流 Maximum reverse current TA= 25°C TA=100°C	I _R	10 100						μA
最大反向恢复时间 MAX. Reverse Recovery Time I _F =0.5A I _R =1.0A I _{RR} =0.25A V _R =10V I _F =50mA R _L =75Ω	trr	50						nS
典型结电容 Type junction capacitance V _R = 4.0V, f = 1MHz	C _j	22				15		pF

特性曲线 Characteristic Curves


正向特性曲线 (典型值)

TYPICAL FORWARD CHARACTERISTIC



正向电流降额曲线

FORWARD CURRENT DERATING CURVE



浪涌特性曲线 (最大值)

MAXIMUM NON REPETITIVE PEAK FORWARD SURGE CURRENT

