



**Sparkle Power Inc.**  
A Leading Power Supply  
Manufacturer  
[www.sparklepower.com](http://www.sparklepower.com)



## R-SPI750ACAG

**(80PLUS Gold, RoHS Compliant)**

**750 Watts ATX12V V2.3 EPS12V V2.92 Switching  
Power Supply (Meet 2013 ErP)**

### Features

- Complied with ATX12V V2.3 EPS12V V2.92 standard
- Active Power Factor Correction (PFC) meet EN61000-3-2
- High efficiency and reliability
- Compatible with European Union Directive 2002/95/EC (Restriction on Hazardous Substances).
- Remote ON/OFF function
- Internal 12V DC fan included
- Noise Killer (thermal fan speed control function)
- Low noise and ripple
- Output over voltage, short circuit, and over current protection
- 100% Hi-pot, ATE, and burn-in tested
- Re-settable power shut down
- Complies with FCC part 15 subpart J class B 115Vac operation, and CISPR 22 class B at 230Vac operation
- Approved by CUL/UL60950-1, TUV EN60950-1, CB 60950-1 report, FCC, EMC.

### Input Characteristics

**Input Range:** 90 ~ 264Vac, Full Range Input

**Frequency:** 47 ~ 63Hz

**Input Current:** Max 10A@100-127Vrms/60Hz  
Max 5A@200-240Vrms/50Hz

**Inrush Current:** No damage.

### Output Characteristics

	MINIMUM LOAD	NORMAL LOAD	MAXIMUM LOAD	LOAD REG.	LINE REG.	RIPPLE & NOISE
+3.3V	0.1A	12A	30/30A	±5%	±1%	50mV P-P
+5V	0.2A	12A	12/30A	±5%	±1%	50mV P-P
+12V1	0.1A	8A	18A	±5%	±1%	120mV P-P
+12V2	0A	8A	18A	±5%	±1%	120mV P-P
+12V3	0A	8A	18A	±5%	±1%	120mV P-P
+12V4	0A	8A	18A	±5%	±1%	120mV P-P
-12V	0A	0.25A	0.5A	±10%	±2%	200mV P-P
+5Vsb	0A	1.5A	3.5A	±5%	±1%	50mV P-P



### Specification

- **Temperature Range:** Operating: +0°C ~ +40°C on full load  
Storage & Shipping: -40°C ~ +70°C
- **Humidity:** 5-85% on operating, 5-95% on storage
- **Dielectric Withstand:** Primary to frame ground 1800V<sub>AC</sub> for 1 second
- **Efficiency:** 87% minimum, typical up to 90%
- **Rise time:** Less than 20ms
- **Hold-up Time:** 17ms minimum at nominal input voltage
- **Power Good Signal:** Power on delay time 100 ~ 500ms, off delay 1ms minimum (TTL and CMOS compatible)
- **Leakage Current:** Less than 3.5mA at 264Vac, 50Hz
- **MTBF:** 100,000 hours on maximum load at +25°C
- **Dimensions (LxWxH):** 140x150x85.8mm / 5.5x5.9x3.4inch

\*+12V1,2,3,4 Peak current is 20A (less than 10mS)

\*+5V<sub>sb</sub> peak current is 4A (less than 0.5S)

\*+3.3V & +5V total output does not exceed 160W  
when +5V is loaded to 30A, then +3.3V maximum load is 3A

when +3.3V is loaded to 30A, then +5V maximum load is 12A

\*+12V1 & +12V2 & +12V3 & +12V4 total output does not exceed 720W(60A)

**Sparkle Power Inc.**

**Main Office**

1000 Rock Avenue

San Jose, CA 95131

Tel : 408-519-8888

Fax: 408-519-9999

E-MAIL: [info@sparklepower.com](mailto:info@sparklepower.com)

**Sparkle Power Inc.**

**Los Angeles Office**

17071 Green Drive

City of Industry, CA 91745

Tel : 626-839-7180

Fax: 626-839-3395