

SMA Female to 7/16 DIN Male Adapter



TECHNICAL DATA SHEET

PE9412

SMA Female to 7/16 DIN Male Adapter

Configuration

Connector 1 SMA Female
Impedance 1 50 Ohms
Connector 2 7/16 DIN Male
Impedance 2 50 Ohms
Adapter Design Standard
Body Style Straight

Mechanical Specifications

Size

Length, in [mm] 1.566 [39.78] Width/Dia., in [mm] 1.25 [31.75]

Connector 1

Type SMA Female
Inner Conductor Material and Plating Gold
Body Material and Plating Brass, Nickel
Dielectric Type PTFE

Connector 2

Type 7/16 DIN Male Inner Conductor Material and Plating Gold
Coupling Nut Material and Plating Brass, Nickel Hex Size, in. 11/4
Torque, in-lbs [Nm] 15 [1.7]
Body Material and Plating Brass, Nickel Dielectric Type PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-7-16-din-male-straight-adapter-pe9412-p.aspx

SMA Female to 7/16 DIN Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE9412 CAD DrawingSMA Female to 7/16 DIN Male Adapter

