






(2,00 mm) .0787"

STMM, ZSTMM SERIES



ZSTMM-112-75-L-D-285



SHROUDED IDC HEADER & STACKER

Mates with:
TCS D

SPECIFICATIONS

For complete specifications and recommended PCB layouts see www.samtec.com?STMM or www.samtec.com?ZSTMM

Insulator Material:
High Temperature Nylon



Terminal Material:
Phosphor Bronze

Plating:
Sn or Au over 50µ" (1,27 µm) Ni

Current Rating:
3A per contact @ 80°C ambient

Operating Temp Range:
-55°C to +105°C with Tin;
-55°C to +125°C with Gold

RoHS Compliant:
Yes

Processing:

Lead-Free Solderable:
Yes

SMT Lead Coplanarity:
(0,10 mm) .004" max

ALSO AVAILABLE

Shrouded board-to-board headers and stackers to mate with SQT, SQW, ESQW and SMM Series. See LTMM and ZLTMM Series.

Note: For added mechanical stability, Samtec recommends mechanical board spacers be used in applications with gold or selective gold plated connectors. Contact ipg@samtec.com for more information.

Note: Other Gold plating options available. Contact Samtec.

Note: This Series is non-standard, non-returnable.

STMM - **1** NO. PINS PER ROW - **02** PLATING OPTION - **D** TAIL OPTION - **OTHER OPTION**

05, 08, 10, 12, 13, 15, 17, 20, 22, 25
(Call Samtec for other sizes)

-F
= Gold flash on post, Matte Tin on tail

-L
= 10µ" (0,25 µm) Gold on post, Matte Tin on tail

-T
= Matte Tin

Leave blank for Through-hole

-RA
= Right Angle

-SM
= Surface Mount

-“XX”
= Polarized Position

-LC
= Locking Clip (-SM only) (Manual placement required)

-K
= (7,50 mm) .295" DIA Film Pick & Place Pad (-SM only)

-TR
= Tape & Reel (-SM only)

ZSTMM - **1** NO. PINS PER ROW - **LEAD STYLE** PLATING OPTION - **D** BODY HEIGHT - **OTHER OPTION**

05, 08, 10, 12, 13, 15, 17, 20, 22, 25
(Call Samtec for other sizes)

Specify LEAD STYLE from chart.

-F
= Gold flash on post, Matte Tin on tail

-L
= 10µ" (0,25 µm) Gold on post, Matte Tin on tail

-T
= Matte Tin

-“XXX”
= Body Height

-“XX”
= Polarized Position

LEAD STYLE	B (OAL)	MAX BODY HEIGHT
-75	(9,58) 0.377	(7,42) 0.292
-62	(10,08) 0.397	(7,92) 0.312
-65	(10,49) 0.413	(8,33) 0.328
-73	(12,09) 0.476	(9,93) 0.391
-63	(14,10) 0.555	(11,94) 0.470
-66	(15,09) 0.594	(12,93) 0.509
-69	(15,60) 0.614	(13,44) 0.529
-74	(17,09) 0.673	(14,94) 0.588
-70	(17,60) 0.693	(15,44) 0.608
-71	(21,08) 0.830	(18,92) 0.745
-72	(21,62) 0.851	(19,46) 0.766

Due to technical progress, all designs, specifications and components are subject to change without notice.

WWW.SAMTEC.COM