




Vinyl Insulated Ring—Expanded Insulation Support



Catalogue numbers with the suffix X indicate an expanded insulation support. This means a wider wire entry to accommodate heavy wall insulation. Ring terminals won't fall free even if the mounting screw loosens.

Stock Thickness:

RA & RB = .03

RC = .04

Cat. No.	Bulk Cat. No.	Pkg. Qty.	Wire Range	Max. Ins.	Wt./lbs. Bolt Hole	Per 1000	Dimensions			
							A	B	C	M
18RA-6X	—	100	22-16	.170	#6	3	.97	.31	.27	.81
18RA-8X	RA867-170	100/1000	22-16	.170	#8	3	.97	.31	.27	.81
18RA-10X	RA877-170	100/1000	22-16	.170	#10	3	.97	.31	.27	.81
18RA-14X	RA727-170	100/1000	22-16	.170	¼"	4	1.13	.50	.37	.88
14RB-4X	—	100	18-14	.200	#4	3	.94	.25	.27	.81
14RB-6X	RB857-200	100/1000	18-14	.200	#6	3	.97	.31	.27	.81
14RB-8X	RB867-200	100/1000	18-14	.200	#8	3	.97	.31	.27	.81
14RB-10X	RB877-200	100/1000	18-14	.200	#10	3	.97	.31	.27	.81
14RB-14X	RB717-200	100/1000	18-14	.200	¼"	4	1.14	.50	.38	.89
14RB-516X	—	100	18-14	.200	⅝"	4	1.15	.50	.38	.89
14RB-38X	—	100	18-14	.200	⅜"	4	1.16	.54	.35	.91
10RC-6X	RC337-250	50/500	12-10	.250	#6	5	1.06	.31	.27	.90
10RC-8X	RC777-250	50/500	12-10	.250	#8	5	1.06	.31	.27	.90
10RC-10X	RC367-250	50/500	12-10	.250	#10	5	1.06	.31	.27	.90
10RC-14X	RC717-250	50/500	12-10	.250	¼"	6	1.16	.50	.27	.90
10RC-516X	—	50	12-10	.250	⅝"	6	1.17	.50	.37	.92
10RC-38X	RC737-250	50/500	12-10	.250	⅜"	6	1.29	.59	.44	.99

U.L. Listed E-9809

Installing tools: WT145C, WT2000, WT112M, ERG-2001, ERG-2003, WT1455, WT2130A (RC, RBC)

Most standard bulk catalogue numbers can be put on Mylar Tape for reel fed applications (12050 tool and application dies). See page C61.

Please put the suffix M for Mylar Tape RA2573M. (Bulk number 1000 and 500 packages.)

For Mil Specs listing, please refer to page C73.