



FEATURES:

- Ideal for use with Amprobe AM-50, AM-71 and Am-1200 Series Digital Multimeters
- Includes Cordura shoulder carrying case
- Test accessories (except spade lugs) comply to IEC 1010-2-031, which is the International Safety Standard for test accessories

MATERIALS:

Model **5914**: Industrial Alligator Clip: Body-Steel, Nickel plated, Insulation- Nylon 6, fire retardant, jaws open to 1".

RATINGS: IEC1010-2-031, Category III, 600 VRMS, 10 Amperes.

All dimensions are in inches. Tolerances (except noted): .xx = $\pm .02$ " (.51 mm), .xxx = $\pm .005$ " (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA

Model **6282**: Test Probe with Stainless Steel Tip: Insulation – Nylon 6, fire retardant, UL94 V-O rated, Probe tip – Stainless Steel, 4mm safety jack: brass, nickel plated, Color: One Black, One Red, **RATINGS**: 1000 VRMS, 10 Amperes

Model **5907A**: Test Lead Straight to Right Angle: Banana Spring: Nickel plated beryllium copper, Insulation–Nylon 6, fire retardant, UL94 V-O, Wire: 48" silicone 18" AWG, Color: One Black, One Red, **RATINGS**: 1000 VRMS, 10 Amperes

Model **6248**: Minigrabber to Sheathed Banana Jack; Grabber: Body: Nylon 6 – Fire Retardant – UL94 V-O Rated, Color per part number, Hook: Beryllium Copper, Gold Plated, Compression Spring: Music Wire, Wire: 18 AWG, 65 x 36 Tinned Copper, Insulation – Silicone, .144" (3,66 mm) O.D., Color per Part Number, Banana Jack: Body - Brass, Nickel Plated, Insulation - Nylon 6, Fire Retardant UL94 V-0 Rated, Color per part number, **RATINGS**: IEC 1010 2-031, Category II, P2 Compliant Voltage: 300 VRMS/DC Max., Current: 5 Amperes Max.

Model **6261**: Minipincer to Sheathed Banana Jack; Grabber: Body: Nylon 6 – Fire Retardant – UL94 V-O Rated, Color per part number, Pincer: Beryllium Copper, Gold Plated, Compression Spring: Music Wire, Wire: 8 AWG, 65 x 36 Tinned Copper, Insulation – Silicone, .144" (3,66 mm) O.D., Color per Part Number
Banana Jack: Body - Brass, Nickel Plated Insulation - Nylon 6, Fire Retardant UL94 V-0 Rated, Color per part number. **RATINGS**: IEC 1010 2-031, Category II, P2 Compliant, Voltage: 300 VRMS/DC Max. Current: 5 Amperes Max.

Model **6203**: Spade Lug: Brass, nickel plated, Insulation - Nylon 6, fire retardant, UL94 V-O, Spade - Nickel plated copper, Color: One Black, One Red, **RATINGS**: 1000 VRMS, 15 Amperes

Model **5910A**: Maxigrabber set with Pincer Tip - **RATINGS**: 1000 VRMS, 10 Amperes, CAT III, P2

Model **5911A**: Maxigrabber set with Hook Tip - **RATINGS**: 1000 VRMS, 10 Amperes, CAT III, P2

ORDERING INFORMATION: Model 6308 (Kit includes items from above)

Replacement P/N's: Model **5914**: Industrial Alligator Clip, Model **6282**: Test Probe with Stainless Steel Tip, Model **5907A**: Test Lead Straight to Right Angle, Model **6248**: Minigrabber to Sheathed Banana Jack, Model **6261**: Minipincer to Sheathed Banana Jack, Model **6203**: Spade Lug, Maxigrabber set with Pincer Tip, Model **5911A**: Maxigrabber set with Hook Tip

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA