

# MOCD207M, MOCD208M

## Dual-channel Phototransistor Small Outline Surface Mount Optocouplers

### Features

- Dual Channel Optocoupler
- Convenient Plastic SOIC-8 Surface Mountable Package Style
- Two Channels in One Compact Surface Mount Package
- Closely Matched Current Transfer Ratios to Minimize Unit-to-Unit Variation
- Minimum  $V_{(BR)CEO}$  of 70 V Guaranteed
- Standard SOIC-8 Footprint, with 0.050" Lead Spacing
- High Input-Output Isolation of 2500 V<sub>AC(rms)</sub> Guaranteed
- Meets U.L. Regulatory Requirements, File #E90700, Volume 2

### Applications

- Feedback Control Circuits
- Interfacing and Coupling Systems of Different Potentials and Impedances
- General Purpose Switching Circuits
- Monitor and Detection Circuits

### Description

The MOCD207M/MOCD208M consist of two silicon phototransistors optically coupled to two GaAs infrared LEDs. These devices are constructed in a small outline surface mount package which conforms to the standard SOIC-8 footprint.

### Schematic




Figure 1. Schematic

### Package Outline




Figure 2. Package Outline

## Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.  $T_A = 25^\circ\text{C}$  unless otherwise specified.

| Symbol              | Rating   | Value       | Unit                       |
|---------------------|--|-------------|----------------------------|
| <b>Emitter</b>      |  |             |                            |
| $I_F$               | Forward Current – Continuous   | 60          | mA                         |
| $I_F$ (pk)          | Forward Current – Peak (PW = 100 $\mu\text{s}$ , 120 pps)  | 1.0         | A                          |
| $V_R$               | Reverse Voltage  | 6.0         | V                          |
| $P_D$               | LED Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above 25°C                                | 90<br>0.8   | mW<br>mW/ $^\circ\text{C}$ |
| <b>Detector</b>     |  |             |                            |
| $V_{CEO}$           | Collector-Emitter Voltage  | 70          | V                          |
| $V_{CBO}$           | Collector-Base Voltage   | 70          | V                          |
| $V_{ECO}$           | Emitter-Collector Voltage  | 7.0         | V                          |
| $I_C$               | Collector Current-Continuous   | 150         | mA                         |
| $P_D$               | Detector Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above 25°C                           | 150<br>1.76 | mW<br>mW/ $^\circ\text{C}$ |
| <b>Total Device</b> |  |             |                            |
| $V_{ISO}$           | Input-Output Isolation Voltage <sup>(1, 2)</sup><br>( $f = 60 \text{ Hz}$ , $t = 1 \text{ minute}$ ) | 2500        | Vac(rms)                   |
| $P_D$               | Total Device Power Dissipation @ $T_A = 25^\circ\text{C}$<br>Derate above 25°C                       | 250<br>2.94 | mW<br>mW/ $^\circ\text{C}$ |
| $T_A$               | Ambient Operating Temperature Range  | -40 to +100 | $^\circ\text{C}$           |
| $T_{stg}$           | Storage Temperature Range  | -40 to +125 | $^\circ\text{C}$           |
| $T_L$               | Lead Soldering Temperature (1/16" from case,<br>10 second duration)                                  | 260         | $^\circ\text{C}$           |

## Electrical Characteristics

$T_A = 25^\circ\text{C}$  unless otherwise specified<sup>(3)</sup>

| Symbol               | Parameter   | Test Conditions   | Device   | Min.      | Typ.* | Max. | Unit          |
|----------------------|---|---|----------|-----------|-------|------|---------------|
| <b>Emitter</b>       |   |   |          |           |       |      |               |
| $V_F$                | Input Forward Voltage                                       | $I_F = 30 \text{ mA}$   | All      |           | 1.25  | 1.55 | V             |
| $I_R$                | Reverse Leakage Current                                     | $V_R = 6.0 \text{ V}$   | All      |           | 0.001 | 100  | $\mu\text{A}$ |
| C                    | Capacitance   |   | All      |           | 18    |      | pF            |
| <b>Detector</b>      |   |   |          |           |       |      |               |
| $I_{CEO}$            | Collector-Emitter Dark Current                              | $V_{CE} = 10 \text{ V}, T_A = 25^\circ\text{C}$                       | All      |           | 1.0   | 50   | nA            |
| $I_{CEO}$            |   | $V_{CE} = 10 \text{ V}, T_A = 100^\circ\text{C}$                      | All      |           | 1.0   |      | $\mu\text{A}$ |
| $V_{(BR)CEO}$        | Collector-Emitter Breakdown Voltage                         | $I_C = 100 \mu\text{A}$   | All      | 70        | 100   |      | V             |
| $V_{(BR)CEO}$        | Emitter-Collector Breakdown Voltage                         | $I_E = 100 \mu\text{A}$   | All      | 7.0       | 10    |      | V             |
| $C_{CE}$             | Collector-Emitter Capacitance                               | $f = 1.0 \text{ MHz}, V_{CE} = 0 \text{ V}$                           | All      |           | 7.0   |      | pF            |
| <b>Coupled</b>       |   |   |          |           |       |      |               |
| CTR                  | Current Transfer Ratio, Collector to Emitter <sup>(4)</sup> | $I_F = 10 \text{ mA}, V_{CE} = 5 \text{ V}$                           | MOCD207M | 100       |       | 200  | %             |
|                      |   |   | MOCD208M | 40        |       | 125  |               |
|                      |   | $I_F = 1 \text{ mA}, V_{CE} = 5 \text{ V}$                            | MOCD207M | 34        |       |      |               |
|                      |   |   | MOCD208M | 13        |       |      |               |
| $V_{CE}(\text{sat})$ | Collector-Emitter Saturation Voltage                        | $I_C = 2.0 \text{ mA}, I_F = 10 \text{ mA}$                           | All      |           |       | 0.4  | V             |
| $t_{on}$             | Turn-On Time  | $I_C = 2.0 \text{ mA}, V_{CC} = 10 \text{ V}, R_L = 100 \Omega$       | All      |           | 3.0   |      | $\mu\text{s}$ |
| $t_{off}$            | Turn-Off Time   | $I_C = 2.0 \text{ mA}, V_{CC} = 10 \text{ V}, R_L = 100 \Omega$       | All      |           | 2.8   |      | $\mu\text{s}$ |
| $t_r$                | Rise Time   | $I_C = 2.0 \text{ mA}, V_{CC} = 10 \text{ V}, R_L = 100 \Omega$       | All      |           | 1.6   |      | $\mu\text{s}$ |
| $t_f$                | Fall Time   | $I_C = 2.0 \text{ mA}, V_{CC} = 10 \text{ V}, R_L = 100 \Omega$       | All      |           | 2.2   |      | $\mu\text{s}$ |
| $V_{ISO}$            | Isolation Surge Voltage <sup>(1)(2)</sup>                   | $f = 60 \text{ Hz}, t = 1 \text{ minute}, I_{I-O} \leq 2 \mu\text{A}$ | All      | 2500      |       |      | Vac(rms)      |
| $R_{ISO}$            | Isolation Resistance <sup>(2)</sup>                         | $V_{I-O} = 500 \text{ V}$   | All      | $10^{11}$ |       |      | $\Omega$      |
| $C_{ISO}$            | Isolation Capacitance <sup>(2)</sup>                        | $V_{I-O} = 0 \text{ V}, f = 1 \text{ MHz}$                            | All      |           | 0.2   |      | pF            |

\*Typical values at  $T_A = 25^\circ\text{C}$

### Notes:

1. Input-Output Isolation Voltage,  $V_{ISO}$ , is an internal device dielectric breakdown rating.
2. For this test, pins 1, 2, 3 and 4 are common and pins 5, 6, 7 and 8 are common.
3. Always design to the specified minimum/maximum electrical limits (where applicable).
4. Current Transfer Ratio (CTR) =  $I_C / I_F \times 100\%$ .

# MOCD207M, MOCD208M — Dual-channel Phototransistor Small Outline Surface Mount Optocouplers

## Typical Performance Curves




Figure 3. LED Forward Voltage vs. Forward Current




Figure 4. Output Current vs. Input Current




Figure 5. Output Current vs. Ambient Temperature




Figure 6. Output Current vs. Collector-Emitter Voltage





Figure 7. Dark Current vs. Ambient Temperature


## Package Dimensions

### 8-pin SOIC Surface Mount



Lead Coplanarity: 0.004 (0.10) MAX

## Recommended Pad Layout



Dimensions in inches (mm).


Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:  
<http://www.fairchildsemi.com/packaging/>

## Ordering Information

| Option | Order Entry Identifier | Description   |
|--------|------------------------|---|
| V      | V                      | VDE Approved  |
| D1     | D1                     | Tape and Reel (500 units per reel), 16 mm Width Carrier Tape                |
| D1V    | D1V                    | VDE Approved, Tape and Reel (500 units per reel), 16 mm Width Carrier Tape  |
| D2     | D2                     | Tape and Reel (2500 units per reel), 16 mm Width Carrier Tape               |
| D2V    | D2V                    | VDE Approved, Tape and Reel (2500 units per reel), 16 mm Width Carrier Tape |
| R2     | R2                     | Tape and Reel (2500 units per reel), 12 mm Width Carrier Tape               |
| R2V    | R2V                    | VDE Approved, Tape and Reel (2500 units per reel), 12 mm Width Carrier Tape |


## Marking Information




### Definitions

|   |  |
|---|--|
| 1 | Fairchild logo   |
| 2 | Device number  |
| 3 | VDE mark (Note: Only appears on parts ordered with VDE option – See order entry table) |
| 4 | One digit year code, e.g., '3'   |
| 5 | Two digit work week ranging from '01' to '53'  |
| 6 | Assembly package code  |

### Carrier Tape Specifications



## Reflow Profile



| Profile Feature   | Pb-Free Assembly Profile |
|---|--------------------------|
| Temperature Minimum (T <sub>smin</sub> )                              | 150°C                    |
| Temperature Maximum (T <sub>smax</sub> )                              | 200°C                    |
| Time (t <sub>s</sub> ) from (T <sub>smin</sub> to T <sub>smax</sub> ) | 60–120 seconds           |
| Ramp-up Rate (t <sub>L</sub> to t <sub>P</sub> )                      | 3°C/second maximum       |
| Liquidous Temperature (T <sub>L</sub> )                               | 217°C                    |
| Time (t <sub>L</sub> ) Maintained Above (T <sub>L</sub> )             | 60–150 seconds           |
| Peak Body Package Temperature   | 260°C +0°C / -5°C        |
| Time (t <sub>P</sub> ) within 5°C of 260°C                            | 30 seconds               |
| Ramp-down Rate (T <sub>P</sub> to T <sub>L</sub> )                    | 6°C/second maximum       |
| Time 25°C to Peak Temperature   | 8 minutes maximum        |



## TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

|                          |  |                                       |                  |
|--------------------------|--|---------------------------------------|------------------|
| 2Cool™                   | FPS™   | PowerTrench®                          | Sync-Lock™       |
| AccuPower™               | F-PFS™   | PowerXS™                              | SYSTEM GENERAL®* |
| AX-CAP®*                 | FRFET®   | Programmable Active Droop™            | TinyBoost™       |
| BitSiC™                  | Global Power Resource™                         | QFET®                                 | TinyBuck™        |
| Build it Now™            | GreenBridge™                                   | QS™                                   | TinyCalc™        |
| CorePLUS™                | Green FPS™                                     | Quiet Series™                         | TinyLogic®       |
| CorePOWER™               | Green FPS™ e-Series™                           | RapidConfigure™                       | TINYOPTO™        |
| CROSSVOLT™               | Gmax™  | Saving our world, 1mW/W/kW at a time™ | TinyPower™       |
| CTL™                     | GTO™   | SignalWise™                           | TinyPWM™         |
| Current Transfer Logic™  | IntelliMAX™                                    | SmartMax™                             | TinyWire™        |
| DEUXPEED®                | ISOPLANAR™                                     | SMART START™                          | TranSiC™         |
| Dual Cool™               | Making Small Speakers Sound Louder and Better™ | Solutions for Your Success™           | TriFault Detect™ |
| EcoSPARK®                | MegaBuck™                                      | SPM®                                  | TRUECURRENT®*    |
| EfficientMax™            | MICROCOUPLER™                                  | STEALTH™                              | µSerDes™         |
| ESBC™                    | MicroFET™                                      | SuperFET®                             | UHC®             |
| Fairchild®               | MicroPak™                                      | SuperSOT™-3                           | Ultra FRFET™     |
| Fairchild Semiconductor® | MicroPak2™                                     | SuperSOT™-6                           | UniFET™          |
| FACT Quiet Series™       | MillerDrive™                                   | SuperSOT™-8                           | VCX™             |
| FACT®                    | MotionMax™                                     | SupreMOS®                             | VisualMax™       |
| FAST®                    | mWSaver™                                       | SyncFET™                              | VoltagePlus™     |
| FastCore™                | OptoHiT™                                       |                                       | XS™              |
| FETBench™                | OPTOLOGIC®                                     |                                       |                  |
|                          | OPTOPLANAR®                                    |                                       |                  |

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

## DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

## LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

## ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, [www.fairchildsemi.com](http://www.fairchildsemi.com), under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

## PRODUCT STATUS DEFINITIONS

### Definition of Terms

| Datasheet Identification | Product Status        | Definition  |
|--------------------------|-----------------------|---|
| Advance Information      | Formative / In Design | Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.   |
| Preliminary              | First Production      | Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design. |
| No Identification Needed | Full Production       | Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.   |
| Obsolete                 | Not In Production     | Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.  |

Rev. I64