



**Pomona  
ACCESS**

**FAX ON DEMAND** This symbol indicates immediate Fax-On-Demand Technical Information is available. Dial (U.S.) (800) 444-6785, (Outside U.S.) (909) 469-2991. Enter the Pomona Access number (shown in italics) when prompted.


## BNC MALE TO UHF MALE, MOLDED STRAIN RELIEF



<i>Pomona ACCESS</i>	Part No.	Length	PRICE
90507	<b>1367-C-18</b>	18"	17.85
	<b>1367-C-24</b>	24"	17.85
	<b>1367-C-36</b>	36"	17.85
	<b>1367-C-48</b>	48"	19.15
	<b>1367-C-60</b>	60"	19.15

RATING: 500 VRMS Max., +50°C (+122°F) Max.  
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.  
BNC/UHF: Body: Brass, Tarnish Resistant Plating  
Contact: Gold Plated Brass


## UHF MALE WITH MOLDED STRAIN RELIEF



<i>Pomona ACCESS</i>	Part No.	Length	PRICE
90821	<b>UHF-C-18</b>	18"	19.95
	<b>UHF-C-24</b>	24"	19.95
	<b>UHF-C-36</b>	36"	19.95
	<b>UHF-C-48</b>	48"	21.00
	<b>UHF-C-60</b>	60"	21.00

RATING: 500 VRMS, +50°C (+122°F) Max.  
CABLE TYPE: 50Ω, RG58C/U, .195" O.D.  
UHF Connector materials same as Model 1367, left.

## BNC MALE TO SMA MALE 50 OHM TEFLON INSULATED CABLE



<i>Pomona ACCESS</i>	Part No.	Length	PRICE
90409	<b>4935-BB-24</b>	24"	34.95
	<b>4935-BB-48</b>	48"	34.95
	<b>4935-BB-60</b>	60"	34.95

RATING: 335 VRMS Max., +165°C (+329°F) Max.  
CABLE TYPE: RG316/U, .098" O.D.  
MATERIAL: SMA: See Model 4846 at right;  
BNC: See Model BNC-C (p. 34)


## SMA MALE 50 OHM CABLE



<i>Pomona ACCESS</i>	Part No.	Cable Type	Length	PRICE
90398	<b>4846-K-24</b>	50Ω, RG174/U, .100" O.D.	24"	34.35
	<b>4846-K-48</b>	Rating +85°C Max.	48"	34.35
	<b>4846-K-60</b>	Loss: .45 dB/ft. at 1.0GHz Max	60"	34.35
	<b>4846-BB-24</b>	50Ω, RG316/U, .098" O.D.	24"	38.45
	<b>4846-BB-48</b>	Rating +200°C Max.	48"	38.45
	<b>4846-BB-60</b>	Loss: .56 dB/ft. at 3.0GHz Max	60"	38.45
	<b>4846-X-24</b>	50Ω, RG142B/U, .195" O.D.	24"	51.00
	<b>4846-X-48</b>	Double Shield	48"	51.00
	<b>4846-X-60</b>	Rating +200°C Max. Loss: .67 dB/ft. at 12.4GHz Max	60"	51.00

SMA: Body/Fittings: Passivated Stainless Steel  
Contact: Gold Plated Brass

## SMA MALE TO SMA MALE RIGHT ANGLE - 50 OHM




SMA Connector materials same as 4846, above right.

<i>Pomona ACCESS</i>	RG 174/U	Length	PRICE
90759	<b>4814-K-24</b>	24"	47.00
	<b>4814-K-48</b>	48"	48.00
	<b>4814-K-60</b>	60"	56.00
	<b>RG 316/U</b>		
	<b>4814-BB-24</b>	24"	53.00
	<b>4814-BB-48</b>	48"	57.00
	<b>4814-BB-60</b>	60"	57.00
	<b>RG 142B/U</b>		
	<b>4814-X-24</b>	24"	56.00
	<b>4814-X-48</b>	48"	68.00
	<b>4814-X-60</b>	60"	68.00

See chart on page 32 for additional cable specifications.

## SMA MALE RIGHT ANGLE 50 OHM CABLE




SMA Connector materials same as 4846 above.

<i>Pomona ACCESS</i>	RG 174/U	Length	PRICE
90758	<b>4813-K-24</b>	24"	50.00
	<b>4813-K-48</b>	48"	53.00
	<b>4813-K-60</b>	60"	53.00
	<b>RG 316/U</b>		
	<b>4813-BB-24</b>	24"	54.00
	<b>4813-BB-48</b>	48"	59.00
	<b>4813-BB-60</b>	60"	59.00
	<b>RG 142B/U</b>		
	<b>4813-X-24</b>	24"	68.00
	<b>4813-X-48</b>	48"	82.00
	<b>4813-X-60</b>	60"	82.00

See chart on page 32 for additional cable specifications.

## SMA MALE TO SMA FEMALE




<i>Pomona ACCESS</i>	RG 174/U	Length	PRICE
90757	<b>4528-K-24</b>	24"	38.70
	<b>4528-K-48</b>	48"	41.00
	<b>4528-K-60</b>	60"	41.00
	<b>RG 316/U</b>		
	<b>4528-BB-24</b>	24"	41.00
	<b>4528-BB-48</b>	48"	47.00
	<b>4528-BB-60</b>	60"	47.00
	<b>RG 142B/U</b>		
	<b>4528-X-24</b>	24"	47.00
	<b>4528-X-48</b>	48"	64.00
	<b>4528-X-60</b>	60"	64.00

SMA material same as Model 4846 above right, except SMA (F): Beryllium Copper center contact

See chart on page 32 for additional cable specifications.

## SMA MALE TO TYPE 'N' MALE 50 OHM CABLE



<i>Pomona ACCESS</i>	Part No.	Length	PRICE
90395	<b>5058-X-12</b>	12"	42.00
	<b>5058-X-24</b>	24"	42.00
	<b>5058-X-36</b>	36"	42.00
	<b>5058-X-48</b>	48"	57.00
	<b>5058-X-60</b>	60"	57.00

RATING: +200°C (+392°F) Max.  
CABLE TYPE: 50Ω, RG142B/U, .195" O.D.  
SMA MATERIAL: See Model 4846 above.  
Type 'N' MATERIAL: See Model 2256 (p. 36).

See chart on page 32 for additional cable specifications.