High Performance BGA Cooling Solutions w/ Thermal Tape Attachment





ATS Part#:

ATS-55150R-C1-R0

Description:

High Performance X-CUT - Heat Sink, T412, BLACK-ANODIZED

Heat Sink Type: Cross-Cut Heat Sink Attachment: Equivalent Part Number: ATS-55150R-C2-R0

THERMAL TAPE

*Image above is for illustration purpose only.

Features & Benefits

- · High efficiency cross-cut fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance .
- . Designed specifically for BGAs and other surface mount packages
- Comes pre-assembled with high performance thermal interface material ٠

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	15.05 °C/W	9.15 °C/W	8.01 °C/W	7.24 °C/W	6.68 °C/W	6.24 °C/W	5.89 °C/W
	Ducted Flow	n/a						

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
	15.0 mm	15.0 mm	19.5 mm	mm	T412	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimensio ATS-551t (Saint Go Thermal p applicatio ATS rese performar ATS certii 	50R-C2-R0 is the ex bain C675). performance data ar n. rves the right to upo nce. fies that this heat sin	height from the botto	nbly with an equivale ence only. Actual pe oducts without notic S-6 and REACH co	ent therman rformanc e to impr	al interface material e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2012 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA