

Non-Shorting Dust Cap for SMA Male




PE6024

TECHNICAL DATA SHEET

Non-Shorting Dust Cap for SMA Male	
Configuration Connector Chain Option	SMA Male Non-Shorting No Chain
Mechanical Specifications Temperature Operating Range, deg C	-65 to +165
Size Length, in [mm] Width, in [mm]	0.327 [8.31] 0.315 [8]
Connector Type Coupling Nut Material and Plating	SMA Male Non-Shorting Brass, Nickel
Coupling Nut Plating Specification Hex Size, Inch Body Material and Plating Body Plating Specification	100µ In. Minimum 5/16 Brass, Nickel 100µ In. Minimum
Compliance Certifications (visit www.Pasterna RoHS Compliant	ck.com for current document) Yes
Plotted and Other Data Notes:	Values at 25 °C, sea level
Non-Shorting Dust Cap for SMA Male from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.	
Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Non-Shorting Dust Cap for SMA Male PE6024	
URL: http://www.pasternack.com/50-ohm-sma-male-non-shorting-cap-pe6024-p.aspx	
PA	

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com





1

PE6024 CAD Drawing Non-Shorting Dust Cap for SMA Male

