


L 252 100 11 P.C.B. connectors

► Expert Range



Male socket.
Vertical closed socket.



Plug
RECTANGULAR SHAPE

Pin 0.8 x 0.8 x 3.4 mm
.031" x .031" x .134"

P.C.B. thickness ≤ 2.4 mm .094"
P.C.B. holes Ø 1.3 mm .051"

Body : UL94 V0 - PA
Grey

Spacing 3.5 mm .138"


Ordering details

N. Poles	Weight kg	Packaging	L. mm	Order code
2	0.0004	200	8.2	1SSA 252 102 R1100
3	0.0005	100	11.7	1SSA 252 103 R1100
4	0.0007	100	15.2	1SSA 252 104 R1100
5	0.0009	100	18.7	1SSA 252 105 R1100
6	0.0011	100	22.2	1SSA 252 106 R1100

Other numbers of poles, consult us

Technical data

	IEC	UL / CSA
Wire size		
Screw		
Solid wire		
Stranded wire		
With ferrule		
Rated voltage	160 V	300 V
Rated current	10 A	10 A
Short-circuit current		
Rated wire size / Gauge		
Storage temperature range	-20 ~ +80 °C	
Insulation resistance	≥ 10 ⁹ Ω	
Wire stripping length		
Recommended screwdriver		
Recommended torque		
Protection		



Socket L 252 100 11
compatible with :



L 242 200 01




Accessories


Rep.	Description	Type	Order code	Packaging	Weight kg
1	Coding peg		1SSA 299 084 R0600	50	0.0005

Other versions, please consult us :


Vertical closed sockets with flanges and inserts.



L 252 100 31



Socket L 252 100 31
compatible with :



L 242 200 01