BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin



ATS Part#:

Description:

Heat Sink Type: Custom Pin Fin Heat Sink Attachment: N/A

Equivalent Part Number: N/A

*Image above is for illustration purpose only.

Features & Benefits

- High efficiency pin fin design provides low pressure drop characteristics
- Large surface area increases heat sink performance
- · Fabricated from extruded aluminum, which minimizes thermal resistance from the base to the fins, reduces weight and keeps costs low

ATS035035008-PF-11G

35.00 x 35.00 x 8.00 mm BGA Heat Sink (High Aspect Ratio Ext.) Custom Pin Fin

· Comes standard without interface material or with most common pressure sensitive thermal tapes as a custom option

Thermal Performance

AIR VELOCITY		@200 LFM 1.0 M/S	@300 LFM 1.5 M/S	@400 LFM 2.0 M/S	@500 LFM 2.5 M/S	@600 LFM 3.0 M/S	@700 LFM 3.5 M/S	@800 LFM 4.0 M/S
THERMAL RESISTANCE	Unducted Flow	9.37 °C/W	6.6 °C/W	5.4 °C/W	4.8 °C/W	4.3 °C/W	4 °C/W	3.7 °C/W
	Ducted Flow	4.5	3.8	3.3	3	2.8	2.6	2.5

Product Detail

Schematic Image	Dimension A	Dimension B	Dimension C	Dimension D	ТІМ	Finish
ning	35.00 mm	35.00 mm	8.00 mm	35 mm	N/A	BLACK-ANODIZED
Image above is for illustration purpose only.	 Dimension Dimension Thermal p application ATS resent performant ATS certifier 	D is fin tip to fin tip performance data are n. ves the right to upda ice. ies that this heat sin	e provided for refere ate or change its pro	m of the base to the nce only. Actual perf ducts without notice -6 and REACH com ble.	formanc to impr	e may vary by

For more information, to find a distributor or to place an order, please contact us at 781-769-2800 (North America), sales@qats.com or www.qats.com.



© 2013 Advanced Thermal Solutions, Inc. | 89-27 Access Road | Norwood MA | 02062 | USA