

# ADVANCE INFORMATION

First Page of Data Sheet in Preparation



## Dual CMOS Analog Switches

### General Description

The MXDG421/423/425 are dual monolithic analog switches. The MXDG421 is normally closed (SPST, NC), while the MXDG423 (SPDT) and MXDG425 (DPST) have two normally-closed and two normally-open poles. These devices feature latching logic inputs that simplify interfacing with microprocessors. All three switches offer low on resistance (35Ω max) over the analog range, fast switching (200ns max), and low power dissipation (0.035mW max). Logic inputs are TTL compatible.

The MXDG421/423/425 are designed with a +44V maximum breakdown voltage rating that allows +30V peak-to-peak switch-off blocking capacity. These switches can be used with a single positive supply (+5V to +30V) or split supplies (±5V to ±20V) while retaining CMOS logic input compatibility and fast switching.

### Applications

- Sample-and-Hold Circuits
- Winchester Disk Drives
- Test Equipment
- Communications Systems
- PBX, PABX
- Guidance and Control Systems
- Heads-Up Displays
- Military Radios
- Battery-Operated Systems

### Features

- ◆ 35Ω Max  $I_{DS(ON)}$
- ◆ 200ns Max Switching
- ◆ 0.035mW Max Power Dissipation
- ◆ CMOS Logic Compatible
- ◆ Operation from Single (+5V to +30V) or Bipolar (±5V to ±20V) Supplies
- ◆ +30V Peak-to-Peak Switch-Off Blocking Capacity


### Ordering Information

PART	TEMP. RANGE	PIN-PACKAGE
MXDG421C/D	0°C to +70°C	Dice*
MXDG421DJ	-40°C to +85°C	16 Plastic DIP
MXDG421DY	-40°C to +85°C	16 Narrow SO
MXDG421DK	-40°C to +85°C	16 CERDIP
MXDG421AK	-55°C to +125°C	16 CERDIP**
MXDG423C/D	0°C to +70°C	Dice*
MXDG423DJ	-40°C to +85°C	16 Plastic DIP
MXDG423DY	-40°C to +85°C	16 Narrow SO
MXDG423DK	-40°C to +85°C	16 CERDIP
MXDG423AK	-55°C to +125°C	16 CERDIP**
MXDG425C/D	0°C to +70°C	Dice*
MXDG425DJ	-40°C to +85°C	16 Plastic DIP
MXDG425DY	-40°C to +85°C	16 Narrow SO
MXDG425DK	-40°C to +85°C	16 CERDIP
MXDG425AK	-55°C to +125°C	16 CERDIP**

\* Contact factory for dice specifications.

\*\* Contact factory for availability and processing to MIL-STD-883.

### Pin Configurations



MXDG421/423/425

1