



PT06 SE (MS3126) SP06 SE straight plug




“SE”, “E”, MS “E” Open Wire Seal




PT06SE-XX-XXX
SP06SE-XX-XXX
PTG06SE-XX-XXX
MS3126E-XX-XXX

TERMINATION ASSEMBLIES
“SE” (SR), MS “F” Strain Relief



PT06SE-XX-XXX (SR)
SP06SE-XX-XXX (SR)
PTG06SE-XX-XXX (SR)
MS3126F-XX-XXX (SR)

“SP”, “P”, MS “P” Potting Boot



PT06SP-XX-XXX
SP06SP-XX-XXX
PTG06SP-XX-XXX
MS3126P-XX-XXX

Shell Size	Plug Front View			Class “SE”, MS/“E”		Plug Side View Class “SE” (SR), MS/“F”			Class “SP”, MS/“P”		
	S Dia. Max.	Z ± .045	Z ₁ ± .045	L Max.	N Max.	L Max.	G Dia.	N Max.	G Dia.	L Max.	N Dia. Max.
8*	.734	.640	.579	1.328	.540	2.413	.125	.828	.327	1.750	.578
10	.859	.640	.579	1.328	.685	2.413	.188	.891	.444	1.750	.734
12	1.031	.640	.579	1.328	.813	2.413	.312	1.016	.558	1.750	.858
14	1.156	.640	.579	1.328	.930	2.413	.375	1.141	.683	1.750	.984
16	1.281	.640	.579	1.328	1.057	2.528	.500	1.203	.808	1.750	1.110
18	1.391	.640	.579	1.328	1.175	2.528	.625	1.469	.909	1.750	1.234
20	1.531	.640	.579	1.297	1.301	2.753	.625	1.469	1.034	1.750	1.360
22	1.656	.640	.579	1.297	1.428	2.753	.750	1.656	1.159	1.750	1.484
24	1.777	.640	.579	1.359	1.533	2.830	.800	1.750	1.284	1.766	1.610

*PT-SE, MS-SE and MS-SP only.
All dimensions for reference only.