

Precision SMA Female to N Female Adapter



TECHNICAL DATA SHEET

PE9432

Precision SMA Female to N Female Adapter

Configuration

Connector 1 **SMA Female** Impedance 1 50 Ohms Connector Specification 1 MIL-C-39012 N Female Connector 2 Impedance 2 50 Ohms Connector Specification 2 MIL-C-39012 Adapter Design Precision Body Style Straight

Electrical Specifications

Frequency Range, GHz DC to 18
Maximum VSWR 1.15:1

Mechanical Specifications

Size

Length, in [mm] 1.5 [38.1] Width/Dia., in [mm] 0.625 [15.88]

Connector 1

Type SMA Female

Connector 2

Type N Female

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/sma-female-n-female-straight-adapter-pe9432-p.aspx

Precision SMA Female to N Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



PE9432 CAD DrawingPrecision SMA Female to N Female Adapter

