

9808	9101	5650	8679
<p>9808-0-15-XX-16-XX-04-0 Press-fit in .067 mounting hole</p>	<p>9101-0-15-XX-16-XX-10-0 Press-fit in .067 mounting hole</p>	<p>5650-0-19-XX-16-XX-10-0 Press-fit in .067 mounting hole</p>	<p>8679-0-15-XX-16-XX-10-0 Solder mount in .071 min. mounting hole</p>

8827	6021	1873
<p>8827-0-15-XX-16-XX-04-0 Press-fit in .061 mounting hole</p>	<p>6021-0-15-XX-16-XX-10-0 Solder mount in .062 min. mounting hole</p>	<p>1873-0-15-XX-16-XX-04-0 Press-fit in .066 mounting hole</p>

--	--	--	--

<p>SPECIFICATIONS</p> <p>SHELL MATERIAL: Brass Alloy 360, 1/2 Hard</p> <p>CONTACT MATERIAL: Beryllium Copper Alloy 172, HT</p> <p>DIMENSION IN INCHES TOLERANCES ON: LENGTHS: ±.005 DIAMETERS: ±.002 ANGLES: ± 2°</p>	<p>ORDER CODE: XXXX - X - 1X - XX - 16 - XX - XX - 0</p> <p>BASIC PART # →</p> <p>SPECIFY SHELL FINISH:</p> <ul style="list-style-type: none"> 01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS) ◇ 15 10μ" GOLD OVER NICKEL (RoHS) <p>SPECIFY CONTACT FINISH:</p> <ul style="list-style-type: none"> 01 200μ" TIN/LEAD OVER NICKEL ◇ 80 200μ" TIN OVER NICKEL (RoHS) ◇ 27 30μ" GOLD OVER NICKEL (RoHS) <p style="text-align: center;">CONTACT</p> <p style="text-align: center;">#16 CONTACT (DATA ON PAGE 221)</p>
--	--

