

## LED LAMP CLUSTER

BL-CR19AR4

### Features:

- Shape: Round
- Diameter: 19mm
- High visibility
- Emitting Color: Red
- No of Built-in 5mm LED Lamps :
- Ultra orange - 4pcs
- Waterproof Package With Hood Suitable
- For Outdoor and Indoor Information Boards
- Rohs Compliance



### Selection Guide

Part No.	Description
BL-CR19AR4	19mm square Lamp cluster 4 red4, square packed

### Description:

- Color Code & Chip characteristics: (Test Condition: IF=20mA)

Part No.	Built-in Lamp Package	Built-in Lamp Part No. BL-L	Chip		Lens Appearance	Electro-optical Data(At 20mA)			Viewing Angle 2 θ 1/2 (deg)
			Material/Emitted Color	Peak Wave Length λ p (nm)		Vf (V)		Iv (mcd)	
						Typ	Max	Typ	
BL-CR19A R4	4x5x7mm 1.0" Lead Oval	563UET	AlGaInP/ Ultra Orange	630	Red Tran.	2.10	2.50	750	X-X 45 Y-Y 25

Notes:

1. θ 1/2 Is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.


### Absolute Maximum Rating (Each Lamp, Ta=25°C Derate above 25°C)

Characteristic	Symbol	Ultra Orang	Ultra Green	Unit
Spectral Line Half width	$\Delta\lambda$	17	30	nm
Pulse Forward Current	IFp	150	150	mA
DC Forward Current	IF	30	30	mA
Reverse Voltage	VR	5	5	V
Power Dissipature	PD	65	75	mW
Operating Temperature	Topr	-40°C -80°C		
Storage Temperature	Tstg	-40°C -85°C		
Lead Soldering Temperature		Max.260±5°C for 3 sec Max. (1.6mm from the base of the epoxy bulb)		

**LED LAMP CLUSTER**

BL-CR19AR4

■ Package configuration & Internal circuit diagram:



WWW


Notes:

- All dimensions are in millimeters (inches)
- Tolerance is  $\pm 0.25(0.01)$  unless otherwise noted.
- Specifications are subject to change without notice.







**LED LAMP CLUSTER**

**BL-CR19AR4**

**Typical electrical-optical characteristics curves:**



- (1) - GaAsP/GaAs 655nm/Red
- (2) - GaP 570nm/Yellow Green
- (3) - GaAsP/GaP 585nm/Yellow
- (4) - GaAsP/GaP 635nm/Orange & Hi-Eff Red
- (5) - GaP 700nm/Bright Red
- (6) - GaAlAs/GaAs 660nm/Super Red
- (8) - GaAsP/GaP 610nm/Super Red
- (9) - GaAlAs 880nm
- (10) - GaAs/GaAs & GaAlAs/GaAs 940nm
- (A) - GaN/SiC 430nm/Blue
- (B) - InGaN/SiC 470nm/Blue
- (C) - InGaN/SiC 505nm/Ultra Green
- (D) - InGaAl/SiC 525nm/Ultra Green



NOTE:25°C free air temperature unless otherwise specified