

2491B Single Core Flexible



Specifications:

Maximum Operating Temperature : 70°C.
 Primary Insulation Material : LSF PVC.
 Secondary Insulation Material : Compound EI5.
 Conductor Material : Copper.
 Approval Bodies : BS6500.
 Approval Category : BASEC.
 Reel Length : 100m.

Specification Table

Primary Insulation Colour	Voltage Rating (V ac)	Core earth/core-core Voltage Rating	Current Rating (A)	Conductor Area CSA (mm ²)	Resistance per Meter (R)	External Diameter	Primary Insulation Thickness	Conductor Make-up*	Part Number	
Brown	300	300/500	3	0.50	39.00	2.12	0.6	16/0.20	PP70	
Blue									PP71	
Black									PP72	
Green/Yellow									PP73	
Brown			6	0.75	26.00	2.33		0.6	24/0.20	PP77
Blue										PP78
Black										PP79
Green/Yellow										PP80
Brown			10	1.00	19.50	2.48		0.6	32/0.20	PP84
Blue										PP85
Black										PP86
Green/Yellow										PP87
Brown	450	450/750	16	1.50	13.30	2.98	0.7	30/0.25	PP91	
Blue								PP92		
Black								PP93		
Green/Yellow								PP94		
Brown			25	2.50	7.98	3.63	0.8	50/0.25	PP98	

Dimensions : Millimetres