

75 Ohm N Female to TNC Male Adapter



PE9628

TECHNICAL DATA SHEET

Configuration Connector 1 Impedance 1 Connector 2 Impedance 2 Adapter Design Body Style **Mechanical Specifications** Size Length, in [mm] Width/Dia., in [mm] **Connector 1** Type Inner Conductor Material and Plating Inner Conductor Plating Specification Body Material and Plating **Body Plating Specification** Dielectric Type **Connector 2** Type Inner Conductor Material and Plating Inner Conductor Plating Specification Coupling Nut Material and Plating Coupling Nut Plating Specification Body Material and Plating **Body Plating Specification Dielectric Type RoHS** Compliant **Plotted and Other Data** Notes: 75 Ohm N Female to TNC Male Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 Phone: (866) 727-8376 or (949) 261-1920 • Fax: (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



industry.

PE9628 REV

75 Ohm N Female to TNC Male Adapter

N Female 75 Ohms **TNC Male** 75 Ohms Standard Straight

1.5 [38.1] 0.665 [16.89]

N Female Brass, Gold 50µ in. minimum Brass, Nickel 100µ in. minimum Teflon

TNC Male Brass, Gold 50µ in. minimum Brass, Nickel 100µ in. minimum Brass, Nickel 100µ in. minimum Teflon

Compliance Certifications (visit www.Pasternack.com for current document) Yes

Values at 25 °C, sea level

URL: http://www.pasternack.com/n-female-tnc-male-straight-adapter-pe9628-p.aspx

PE9628 CAD Drawing 75 Ohm N Female to TNC Male Adapter

