

AD845

FEATURES

Replaces Hybrid Amplifiers in Many Applications

AC PERFORMANCE:

Settles to 0.01% in 350 ns

100 V/ μ s Slew Rate

12.8 MHz min Unity-Gain Bandwidth

1.75 MHz Full-Power Bandwidth at 20 V p-p

DC PERFORMANCE:

0.25 mV max Input Offset Voltage

5 μ V/ $^{\circ}$ C max Offset Voltage Drift

0.5 nA Input Bias Current

250 V/mV min Open-Loop Gain

4 μ V p-p max Voltage Noise, 0.1 Hz to 10 Hz

94 dB min CMRR

Available in Plastic Mini-DIP, Hermetic Cerdip and SOIC Packages. Also Available in Tape and Reel in Accordance with EIA-481A Standard


PRODUCT DESCRIPTION

The AD845 is a fast, precise, N channel JFET input, monolithic operational amplifier. It is fabricated using Analog Devices' complementary bipolar (CB) process. Advanced laser-wafer trimming technology enables the very low input offset voltage and offset voltage drift performance to be realized. This precision, when coupled with a slew rate of 100 V/ μ s, a stable unity-gain bandwidth of 16 MHz, and a settling time of 350 ns 0.01%—while driving a parallel load of 100 pF and 500 Ω —represents a combination of features unmatched by any FET input IC amplifier. The AD845 can easily be used to upgrade many existing designs which use BiFET or FET input hybrid amplifiers and, in some cases, those which use bipolar input op amps.


The AD845 is ideal for use in applications such as active filters, high speed integrators, photo diode preamps, sample-and-hold amplifiers, log amplifiers, and in buffering A/D and D/A converters. The 250 μ V max input offset voltage makes offset nulling unnecessary in many applications. The common-mode rejection ratio of 110 dB over a ± 10 V input voltage range represents exceptional performance for a JFET input high speed op amp. This, together with a minimum open-loop gain of 250 V/mV ensures that 12-bit performance is achieved, even in unity-gain buffer circuits.

CONNECTION DIAGRAMS

Plastic Mini-DIP (N) Package
and Cerdip (Q) Package



16-Pin SOIC
(R-16) Package



The AD845 conforms to the standard op amp pinout except that offset nulling is to $V+$. The AD845J and AD845K grade devices are available specified to operate over the commercial 0 to $+70^{\circ}$ C temperature range. AD845A and AD845B devices are specified for operation over the -40° C to $+85^{\circ}$ C industrial temperature range. The AD845S is specified to operate over the full military temperature range of -55° C to $+125^{\circ}$ C. Both the industrial and military versions are available in 8-pin cerdip packages. The commercial version is available in an 8-pin plastic mini-DIP and 16-pin SOIC; "J" and "S" grade chips are also available.

PRODUCT HIGHLIGHTS

1. The high slew rate, fast settling time, and dc precision of the AD845 make it ideal for high speed applications requiring 12-bit accuracy.
2. The performance of circuits using the LF400, HA2520/2/5, HA2620/2/5, 3550, OPA605, and LH0062 can be upgraded in most cases.
3. The AD845 is unity-gain stable and internally compensated.
4. The AD845 is specified while driving 100 pF/500 Ω loads.

SPECIFICATIONS (@ +25°C and ±15 V dc, unless otherwise noted)

AD845

Model	Conditions	AD845J/A			AD845K/B			AD845S			Units
		Min	Typ	Max	Min	Typ	Max	Min	Typ	Max	
INPUT OFFSET VOLTAGE ¹	Initial Offset		0.7	1.5		0.1	0.25		0.25	1.0	mV
	Offset Drift	T_{min} - T_{max}		2.5 20		1.5	0.4 5.0		2.0 10		mV μ V/°C
INPUT BIAS CURRENT ²	Initial	$V_{CM} = 0$ V	0.75	2	0.5	1	0.75	2	nA		
		T_{min} - T_{max}		45/75		18/38		500	nA		
INPUT OFFSET CURRENT	Initial	$V_{CM} = 0$ V	25	300	15	100	25	300	pA		
		T_{min} - T_{max}		3/6.5		1.2/2.6		20	nA		
INPUT CHARACTERISTICS	Input Resistance		10 ¹¹		10 ¹¹		10 ¹¹		k Ω		
	Input Capacitance		4.0		4.0		4.0		pF		
INPUT VOLTAGE RANGE	Differential		± 20		± 20		± 20		V		
	Common Mode		± 10	+ 10.5/-13	± 10	+ 10.5/-13	± 10	+ 10.5/-13	V		
	Common-Mode Rejection	$V_{CM} = \pm 10$ V	86	110	94	113	86	110	dB		
INPUT VOLTAGE NOISE	0.1 to 10 Hz		4		4		4		μ V p-p		
	f = 10 Hz		80		80		80		nV/ $\sqrt{\text{Hz}}$		
	f = 100 Hz		60		60		60		nV/ $\sqrt{\text{Hz}}$		
	f = 1 kHz		25		25		25		nV/ $\sqrt{\text{Hz}}$		
	f = 10 kHz		18		18		18		nV/ $\sqrt{\text{Hz}}$		
	f = 100 kHz		12		12		12		nV/ $\sqrt{\text{Hz}}$		
INPUT CURRENT NOISE	f = 1 kHz		0.1		0.1		0.1		pA/ $\sqrt{\text{Hz}}$		
OPEN-LOOP GAIN	$V_O = \pm 10$ V		200	500	250	500	200	500	V/mV		
	$R_{LOAD} \geq 2$ k Ω		100	250	125	250	100	250	V/mV		
	$R_{LOAD} \geq 500$ Ω		70		75		50		V/mV		
	T_{min} - T_{max}										
OUTPUT CHARACTERISTICS	Voltage	$R_{LOAD} \geq 500$ Ω	± 12.5		± 12.5		± 12.5		V		
	Current	Short Circuit	50		50		50		mA		
	Output Resistance	Open Loop	5		5		5		Ω		
FREQUENCY RESPONSE	Small Signal	Unity Gain	12.8	16	13.6	16	13.6	16	MHz		
	Full Power Bandwidth ³	$V_O = \pm 10$ V $R_{LOAD} = 500$ Ω		1.75		1.75		1.75	MHz		
	Rise Time			20		20		20	ns		
	Overshoot			20		20		20	%		
	Slew Rate		80	100	94	100	94	100	V/ μ s		
	Settling Time	10 V Step $C_{LOAD} = 100$ pF $R_{LOAD} = 500$ Ω to 0.01% to 0.1%		350		350	500	350	500	ns	
				250		250		250	ns		
DIFFERENTIAL GAIN	f = 4.4 MHz		0.04		0.04		0.04		%		
DIFFERENTIAL PHASE	f = 4.4 MHz		0.02		0.02		0.02		Degree		
POWER SUPPLY	Rated Performance		± 4.75	± 15	± 4.75	± 15	± 4.75	± 15	V		
	Operating Range		88	110	95	113	88	110	V		
	Rejection Ratio	$V_S = \pm 5$ to ± 15 V		10	12	10	12	10	12	dB	
	Quiescent Current	T_{min} to T_{max}								mA	

9
NOTES
¹Input offset voltage specifications are guaranteed after 5 minutes of operation at $T_A = +25^\circ\text{C}$.

²Bias current specifications are guaranteed maximum at either input after 5 minutes of operation at $T_A = +25^\circ\text{C}$.

³FPBW = slew rate/ 2π V peak.

⁴"S" grade T_{min} - T_{max} are tested with automatic test equipment at $T_A = -55^\circ\text{C}$ and $T_A = +125^\circ\text{C}$.

All min and max specifications are guaranteed. Specifications shown in **boldface** are tested on all production units at final electrical test. Results from these tests are used to calculate outgoing quality levels.

Specifications subject to change without notice.

AD845

ABSOLUTE MAXIMUM RATINGS¹

Supply Voltage	±18 V
Internal Power Dissipation ²	
Plastic Mini-DIP	1.6 Watts
Cerdip	1.4 Watts
16-Pin SOIC	1.5 Watts
Input Voltage	±V _S
Output Short-Circuit Duration	Indefinite
Differential Input Voltage	+V _S and -V _S
Storage Temperature Range	
Q	-65°C to +150°C
N, R	-65°C to +125°C
Lead Temperature Range (Soldering 60 sec)	+300°C


NOTES

¹Stresses above those listed under "Absolute Maximum Ratings" may cause permanent damage to the device. This is a stress rating only, and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

²Mini-DIP package: $\theta_{JA} = 100^\circ\text{C}/\text{W}$; cerdip package: $\theta_{JA} = 110^\circ\text{C}/\text{W}$; SOIC package: $\theta_{JA} = 100^\circ\text{C}/\text{W}$.

METALIZATION PHOTOGRAPH

Dimensions shown in inches and (mm).
Contact factory for latest dimensions.



ORDERING GUIDE

Model	Temperature Range	Package Description	Package Option*
AD845JN	0°C to +70°C	8-Pin Plastic Mini-DIP	N-8
AD845KN	0°C to +70°C	8-Pin Plastic Mini-DIP	N-8
AD845JR	0°C to +70°C	16-Pin SOIC	R-16
AD845AQ	-40°C to +85°C	8-Pin Cerdip	Q-8
AD845BQ	-40°C to +85°C	8-Pin Cerdip	Q-8
AD845SQ	-55°C to +125°C	8-Pin Cerdip	Q-8
AD845SQ/883B	-55°C to +125°C	8-Pin Cerdip	Q-8
5962-8964501PA	-55°C to +125°C	8-Pin Cerdip	Q-8
AD845J Chips	0°C to +70°C	Die	
AD845S Chips	-55°C to +125°C	Die	
AD845JR-Reel	0°C to +70°C	Tape & Reel	

*N = Plastic DIP; Q = Cerdip; R = Small Outline IC (SOIC). For outline information see Package Information section.