



Rectifier Diode Modules

VRRM 800 to 1800V


IFAV 400 Amp

Applications

- Non-controllable rectifiers for AC/AC converters
- Line rectifiers for transistorized AC motor controllers
- Field supply for DC motors

Features

- Blocking voltage: 800 to 1800V
- Heat transfer through aluminum nitride ceramic isolated metal baseplate



Module Type

TYPE			VRRM	V _{RSM}
MSCD400-08	MSAD400-08	MSKD400-08	800V	900V
MSCD400-12	MSAD400-12	MSKD400-12	1200V	1300V
MSCD400-16	MSAD400-16	MSKD400-16	1600V	1700V
MSCD400-18	MSAD400-18	MSKD400-18	1800V	1800V

Maximum Ratings

Symbol	Conditions	Values	Units
IFAV	T _c =85°C	400	A
IFSM	t=10mS T _{vj} =45°C	15000	A
i ² t	t=10mS T _{vj} =45°C	1125000	A ² s
V _{isol}	a.c.50HZ;r.m.s.;1min	3000	V
T _{vj}		-40 to +150	°C
T _{stg}		-40 to +125	°C
Mt	To terminals(M10)	9±15%	Nm
Ms	To heatsink(M6)	5±15%	Nm
Weight	Module	1509	g

Thermal Characteristics

Symbol	Conditions	Values	Units
R _{th(j-c)}	Module	0.05	°C/W
R _{th(c-s)}	Module	0.02	°C/W

Electrical Characteristics

Symbol	Conditions	Values	Units
V _{FM}	T=25°C I _{FM} =1200A	1.8	V
I _{RD}	T _{vj} =T _{vjM} V _{RD} =V _{RRM}	≤20	mA

Performance Curves




Fig1. Forward Characteristics




Fig2. Transient thermal impedance




Fig3. Power dissipation




Fig4. case temperature vs. forward current




Fig5. Max Non-Repetitive Forward Surge Current

Package Outline Information

