

multicomp	PART NO.		REVISIONS							
	7001-4P4C	ECN #	REV	DESCRIPTION	DRAWN	DATE	CHECKD	DATE	APPRVD	DATE
		-	А	RELEASED	Ramya	31/08/09	Naveen	31/08/09	Farnell	14/09/09





Specifications:

Current rating Voltage rating Maximum contact resistance Minimum insulator resistance Withstanding voltage Operating temperature range **Material and finish:** Insulator Contact Plating 쇟




: 20mΩ. : 1000MΩ.

: 1.0A ac/dc.

: 150V ac/dc

- : 500V ac for one minute.
- : -40°C to +125°C.
- : High temperature plastic.
- : Phosphor bronze.
- : Gold plated.



For flat cable

Dimensions : Millimetres

Part Number Table

Description	Part Number			
Plug, RJ11, 4P4C, Flat	7001-4P4C			

This data sheet and its contents (the "Information") belong to the Premier Farnell Group (the "Group") or are licensed to it. No licence is granted for the use of it other than for	TOLERANCES:	DRAWN BY:	DATE:	DRAWING TITLE:				
completeness, any error in or ormission from it or nor any use made of it. Users of the prod- data sheet should check for themselves the Information and the subability of the prod- ucts for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or	UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE FOR REFERENCE PURPOSES ONLY.	Ramya	31/08/09	RJ11 Modular Plug - 4P4C				
		CHECKED BY:	DATE:	SIZE DWG NO.	M10002362	ELECTRONIC FILE	REV A	
		Naveen	31/08/09			1712384-DWG		
		APPROVED BY:	DATE:				OF 2	
		Farnell	14/09/09	SCALE: NTS	U.O.M.: mm	SHEET: 1 OI		