

SMA Male to SSMA Female Adapter



TECHNICAL DATA SHEET

SMA Male to SSMA Female Adapter Configuration Connector 1 SMA Male Impedance 1 50 Ohms Connector 2 50 Ohms Impedance 2 Adapter Design Standard Body Style Straight Mechanical Specifications Size Length, in [mm] 0.705 [17.91] Width/Dia., in [mm] **Connector 1** SMA Male Type Inner Conductor Material and Plating Gold Coupling Nut Material and Plating Hex Size, in 5/16 Torque, in-lbs [Nm] 8 [0.9] Body Material and Plating **Dielectric Type** PTFE **Connector 2** Type Inner Conductor Material and Plating Gold Body Material and Plating **Dielectric Type** PTFE Compliance Certifications (visit www.Pasternack.com for current document) **RoHS** Compliant Yes **Plotted and Other Data** Notes: Values at 25 °C, sea level URL: http://www.pasternack.com/sma-male-ssma-female-straight-adapter-pe9063-p.aspx

SSMA Female

0.312 [7.92]

Passivated Stainless Steel Passivated Stainless Steel

SSMA Female Passivated Stainless Steel

SMA Male to SSMA Female Adapter from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



industry.

PE9063

PE9063 CAD Drawing

SMA Male to SSMA Female Adapter

