



## 20-30W Universal 3-Wire Input Desktop Adapter PSAC30U Adapter Meets Ecodesign and EISA Requirements



### Features

- Low Cost
- EISA Energy Efficiency Compliance
- Ecodesign ErP Directive 2009/125/EC level 2 annex 1b compliant
- Non-Vented Case
- Class B EMI
- Low Profile Design
- Compact Size

### Applications

- Portable Equipment
- Peripherals
- Networking
- Gaming Machines

### Safety Approvals

- CE
- Meeting Cal. Prop. 65
- cUL/UL

### Mechanical Characteristics

- Length: 103.4mm (4.07in.)
- Width: 42mm (1.65in.)
- Height: 28.7mm (1.13in.)
- Weight: 160g (5.64oz)

### Output Specifications

Model	DC Output Voltage	Load		Ripple*	Output Power	Efficiency Level
		Min.	Max.			
PSAC30U-050	5V	0A	4.00A	70mV	20W	ⓧ
PSAC30U-120	12V	0A	2.50A	120mV	30W	ⓧ
PSAC30U-240	24V	0A	1.25A	240mV	30W	ⓧ
PSAC30U-560	56V	0A	0.54A	560mV	30W	ⓧ

Note (\*): Measured with by-pass capacitors 0.1uF//10uf at output connector terminal and oscilloscope set at 20MHz.

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at [www.phihong.com](http://www.phihong.com) for the most up-to-date specifications and contact information.

**INPUT:**

**AC Input Voltage Rating**  
100 to 240VAC

**AC Input Voltage Range**  
90 to 264VAC

**AC Input Current**  
0.8A (RMS) maximum at 120VAC  
0.5A (RMS) maximum at 240VAC

**In-rush Current**  
60A maximum at 100VAC  
100A maximum at 240VAC

**AC Input Frequency**  
47 to 63Hz

**Leakage Current**  
3.5mA maximum at 254VAC, 50Hz

**Input Power Saving**  
<0.3W maximum

**OUTPUT**  
**Output Power**  
30W

**Efficiency**  
Meets level V Efficiency Marking  
78.6% min. at 5V, 83.5% min at 12V, 24V and 56V

**ENVIRONMENTAL:**

Operating Temperature           0 to 40°C  
Storage Temperature            -20 to 75°C

Operating Humidity               20 to 90%

**EMI**

FCC Class B  
EN55022 Class B

**Immunity**

EN61000-4-2	Level 4
EN61000-4-3	Level 2
EN61000-4-4	Level 2
EN61000-4-5	Level 3
EN61000-4-6	Level 2
EN61000-4-8	Level 1
EN61000-4-11	

**High-pot Test**

Input to output: 3000VAC, 10mA for 1 minute  
Input to F.G.: 1500VAC, 10mA for 1 minute

**Insulation Resistance**

Input to Output: >7M ohm 500VDC  
Input to F.G.: >7M ohm 500VDC

**Over Current Protection**

Auto restart without damage

**Over Voltage Protection**

160% maximum

**Short Circuit Protection**

Output can be shorted permanently without damage

**MTBF**

50K hours min at full load and 25°C ambient

**AC Input Connector**

IEC C14

**DC Output Connector**

5.5 x 2.1 x 10mm Center Positive Barrel

**Dimension Diagram Unit: mm (inch)**

